

SURVEY & REMONUMENTATION

JAN 13 1998

SECTION

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

IRON COUNTY
MICHIGAN
RECEIVED FOR RECORD

97 DEC 23 PM 1:28
L.C. Records 4.7 P. 142

Edmund J. Pisoni
REGISTER OF DEEDS

For corners in

Iron
(County)

Located In:

Corner Code #

1. Public Land Survey

T 44N R 32W

CD-7

T R

003

T R

T R

T R

2. Property Controlling
in Section

S T R

S T R

3. Miscellaneous

S T R

Property in Sec.

S T R

Register of Deeds Stamp & File Number

4. Lot No. , Recorded Plat

5. Private Claims

West Meander Corner Sections 17 and 20, T44N, R32W

I, Gary L. Pisoni, in a field survey on November 13, 1997 do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and /or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

Original corner established in 1849 by Zelotes B. Searls, U.S. Deputy Surveyor.

Original Corner; Wood Post

Original Bearing Trees:

Cedar

8"

N10° W

12 lks.(7.92 feet)

Tamarack

10"

S05° W

10 lks.(6.60 feet)

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

No original corner evidence was recovered.

Set a W.C. M.C. on line between the SW corner of Section 17 and the East Meander Corner between Sections 17 and 20. W.C. M.C. is located 14 feet from edge of shoreline.

Corner record research on file with County Representative.

PEER GROUP APPROVED
Gary L. Pisoni 12-01-97
IRON COUNTY REPRESENTATIVE

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

At the W.C. M.C. corner position, set a 3/4 inch diameter aluminum rod monument, 7 feet long, 6 inches above the ground surface, with a 3 inch diameter aluminum cap stamped as follows: Iron County Remonumentation, T44N, R32W, S17, S20, W.C. M.C., N 89° 39'37"E, 16.90', 1997, RLS 27457. Blazed and scribed the following new bearing trees;(Measurements are taken to a nail in side of tree)

Black Spruce

6"

N33° E

15.37 feet

Black Spruce

5"

S34° E

22.30 feet

Tamarack

7"

S50° W

35.32 feet

Black Spruce

6"

N55°W

19.60 feet

Steel Sign Post

East

0.82 feet

97-37

Signed by *Gary L. Pisoni*

Date November 29, 1997

Surveyor's Michigan License No. 27457

FORM APPROVED BY MICHIGAN STATE BOARD OF PROFESSIONAL SURVEYORS, JAN. 28, 1971

