

LAND CORNER RECORDATION CERTIFICATE  
Filing Requirement of Act 74, Mich. P.A. 1970 as Amended

For corners in

| Iron<br>(County)                      | Located In:      | Corner Code # |
|---------------------------------------|------------------|---------------|
| 1. Public Land Survey                 | T R              |               |
|                                       | T R              |               |
|                                       | T R              |               |
| 2. Property Controlling<br>in Section | S 12 T 44N R 33W | 12            |
|                                       | S T R            | (GCDB 640520) |
|                                       | S 12 T 44N R 33W | 16            |
| 3. Miscellaneous<br>Property in Sec.  | S T R            | (GCDB 660500) |
|                                       | S T R            |               |
| 4. Lot No. _____, Recorded Plat       |                  |               |
| 5. Private Claims                     |                  |               |

Register of Deeds Stamp & File Number

|    | A | B  | C | D  | E | F  | G | H  | I | J  | K | L  | M |
|----|---|----|---|----|---|----|---|----|---|----|---|----|---|
| 1  |   |    |   |    |   |    |   |    |   |    |   |    |   |
| 2  |   | 6  |   | 5  |   | 4  |   | 3  |   | 2  |   | 1  |   |
| 3  |   |    |   |    |   |    |   |    |   |    |   |    |   |
| 4  |   | 7  |   | 8  |   | 9  |   | 10 |   | 11 |   | 12 |   |
| 5  |   |    |   |    |   |    |   |    |   |    |   |    |   |
| 6  |   | 18 |   | 17 |   | 16 |   | 15 |   | 14 |   | 13 |   |
| 7  |   |    |   |    |   |    |   |    |   |    |   |    |   |
| 8  |   | 19 |   | 20 |   | 21 |   | 22 |   | 23 |   | 24 |   |
| 9  |   |    |   |    |   |    |   |    |   |    |   |    |   |
| 10 |   | 30 |   | 29 |   | 28 |   | 27 |   | 26 |   | 25 |   |
| 11 |   |    |   |    |   |    |   |    |   |    |   |    |   |
| 12 |   | 31 |   | 32 |   | 33 |   | 34 |   | 35 |   | 36 |   |
| 13 |   |    |   |    |   |    |   |    |   |    |   |    |   |



I, Stephan J. Szyszkoski, in a field survey on 02/23/16 do hereby state  
that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2  
above were in conformance with regulations and rules therefore as required in the current manual of survey  
instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of  
a Court of Law and /or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with  
the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established,  
re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded  
on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

(12-Sec. 12) Center-South 1/16 corner, Section 12. Not previously monumented.

(16-Sec. 12) East 1/16 corner between Sections 12 and 13. Not previously monumented.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

(12-Sec. 12) Established the position for the corner midway and on a straight line between Quarter  
corner 1336.30' south and Center of Section 12 1336.30' north. The position for the corner falls in  
a marsh and is not accessible. Established a witness corner on the N-S 1/4 line 247.00' south of  
the corner position.

(16-Sec. 12) Established the position for the corner midway and on the Section line between Section  
corner 1309.72' east and Quarter corner 1309.72' west.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

(12) Set 1"IDx28" I.pipe with 2" alum. MDNR cap  
247.00' south of the corner position for a W.C.  
Set measuring nail with MDNR tag in the side of:  
4" Balsam N89°E 23.3' mrkd "WC BT"  
11" B.Spruce S82°W 26.45' do  
3" Balsam N77°W 8.45' do  
2" B.Spruce S72°E 10.8' "X X"  
Set sq'd cedar post adjacent.  
E= 7893726.201 N= 160648.900

(16) Set 1"IDx28" I.pipe with 2" alum. MDNR cap.  
Set measuring nail with MDNR tag in the side of:  
18" Cedar S65°E 26.7' mrkd "1/16S BT"  
20" Cedar S11°E 19.0' do  
6" Balsam S07°W 14.45' do  
Fd. a 4' tall iron T post East 14.7'  
Set sq'd cedar post adjacent.  
E= 7894120.769 N= 160320.069

Bearings are magnetic. Coordinates are MCS83 in meters, NAD83(2011) Epoch 2010.00 datum.  
Coord. Ref.=NGS PID AA8081: N= 147176.694 m. E= 7895147.461 m.

Signed by Stephan J. Szyszkoski Date 03/01/2016  
Surveyor's Michigan License No. 33986

For the Michigan Department of Natural Resources, Forest Resources Division