

# SURVEY & REMONUMENTATION

FEB 21 2001

## SECTION

### LAND CORNER RECORDATION CERTIFICATE Filing Requirement of Act 74, Mich. P.A. 1970

For corners in

_____ Iron _____	Located In:	Corner Code #
(County)		
1. Public Land Survey	T <u>44N</u> R <u>33W</u>	<u>K-9</u>
	T _____ R _____	_____
	T _____ R _____	_____
	T _____ R _____	_____
2. Property Controlling	S _____ T _____ R _____	_____
in Section	S _____ T _____ R _____	_____
3. Miscellaneous	S _____ T _____ R _____	_____
Property in Sec.	S _____ T _____ R _____	_____

COMMENCING YEAR 2000  
RECEIVED FOR RECORD  
IRON COUNTY, MICHIGAN

00 DEC -8 PM 1: 10

L.C. Records: L.S. P. 285

*Gary L. Pisoni*  
REGISTERED LAND SURVEYOR

Register of Deeds Stamp & File Number

4. Lot No. \_\_\_\_\_, Recorded Plat \_\_\_\_\_  
5. Private Claims \_\_\_\_\_

Section Corner to Sections 23, 24, 25, 26, T44N, R33W

I, Gary L. Pisoni, in a field survey on November 21, 2000 do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2	6		5		4		3		2		1		
3													
4	7		8		9		10		11		12		
5													
6	18		17		16		15		14		13		
7													
8	19		20		21		22		23		24		
9													
10	30		29		28		27		26		25		
11													
12	31		32		33		34		35		36		
13													

#### A. Description of original monument and accessories and/or subsequent restoration:

Original corner established in June, 1851 by Guy H. Carleton, U.S. Deputy Surveyor.

Original Corner; Wood Post

Original Bearing Trees:

Lynn	12"	N 28° E	30 links (19.80 feet)
Sugar	14"	S 22° E	39 links (25.74 feet)

#### B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

No evidence of original B.T.s found.

Restored the corner position by double proportionate measurement between the Northeast corner of Section 25 and the Northwest corner of Section 26 and between the Southwest corner of Section 25 and the Northwest corner of Section 24.

Found a blue painted tree used as the Section corner which bears S 37°34'W and 198.83 feet from the double proportioned corner.

Corner record research on file with County Representative:

PEER GROUP APPROVED

*Gary L. Pisoni* 11-30-2000

COUNTY REPRESENTATIVE

#### C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

At the corner position, set a 5/8" diameter by 30" long rebar, flush with ground surface, with a 3" diameter aluminum cap stamped as follows: Iron County Remonumentation, T44N, R33W, S-23, S-24, S-25, S-26, 2000, RLS 27457 from which I established the following new blazed and scribed bearing trees: (All measurements taken to a nail in side of tree)

Red Maple	10"	N 36° E	30.54 feet
Sugar Maple	8"	S 63° E	19.06 feet
Sugar Maple	7"	S 01° W	17.69 feet
Sugar Maple	7"	S 82° W	9.12 feet
Steel sign post		N 43° W	0.7 feet

00-053

Signed by Gary L. Pisoni

Date 11-29-2000

Surveyor's Michigan License No. 27457

FORM APPROVED BY MICHIGAN STATE BOARD OF PROFESSIONAL SURVEYORS, JAN. 28, 1971  
REVISED MAY 14, 1975  
REVISED JAN., 1983  
REVISED OCT., 1995

