

LAND CORNER RECORDATION CERTIFICATE
FILING REQUIREMENT OF ACT 74, MICH. P.A. 1970

| (IRON COUNTY) | | CORNER CODE NUMBER |
|--|---|--------------------|
| FOR CORNERS OF—: | LOCATED IN—: | |
| 1. PUBLIC LAND SURVEY _____ | T. <u>44</u> ^{N.} S. , R. <u>34</u> ^{W.} E. | C-11 |
| 2. PROPERTY CONTROLLING IN SECTION _____ | , T. _____ ^{N.} S. , R. _____ ^{E.} W. | |
| 3. MISCELLANEOUS PROPERTY IN SECTION _____ | , T. _____ ^{N.} S. , R. _____ ^{E.} W. | |
| 4. LOT NO. _____, RECORDED PLAT _____ | | |
| 5. PRIVATE CLAIMS _____ | | |

REGISTER OF DEEDS STAMP AND
FILING NUMBER

I, Arthur O. Enger, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were, in a field survey on August 29, 19 77, established, re-established, monumented, re-monumented, recovered or restored as expressed below and in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a court of law. Furthermore, that the corner points mentioned in lines 3, 4 and 5 above were, in a field survey on _____, 19____, found, recovered, restored, established or re-established as expressed below and in conformance with the rules of the Michigan State Board of Registration for Land Surveyors or, by a Decree of a Court of law:

A. Description of original monument and accessories and/or subsequent restoration:

Corner C11 (Section Corner 29, 30, 31, & 32, T44N, R34W):

| | |
|------------------|---|
| Wood post | (Not found. No subsequent monuments found.) |
| Sugar 12 S28E 38 | (" " " " accessories ") |
| Sugar 6 N14W 14 | (" " " " " ") |

B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:

Corner C11: Restored by double proportionate measurements from corners N0°31.2'E 80.133 ch., S0°44.5'E 80.137 ch., S88°01.1'E 40.321 ch., and S89°35.8'W 78.980 ch.* Corner thus set falls in the road bed of a N & S county road. *The last named corner is an estimated position, extrapolated southward from an original line tree 71.55 ch. N, on the average bearing of the lines between the line tree and original corners 0.1 mile, 0.6 mile, 1.1 miles, 1.6 miles, 2.1 miles, 3.1 miles, and 7.1 miles north of it, and at the extrapolated proportionate distance. It probably is not exact, but is not likely to be greatly in error, and since using it caused the corner to fall in a position compatible with common report (the road), I have felt it to be about as accurate as the original survey of this township was in the first place.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

Corner C11: 1" I.D. x 24" iron pipe with 3 3/4" aluminum cap.
Sugar Maple 10 S60°W (mag.) 52.4 ft. "S31, NBT"
Red Maple 12 N33°W (mag.) 36.9 ft. "S30, NBT"
Red Maple 12 S58°E (mag.) 55.7 ft. "S31, NBT"
Declination is 0°05' West

SIGNED BY _____ DATE _____

SURVEYOR'S MICHIGAN REGISTRATION NO. _____

(SEAL)

FOR STATE AND UNITED STATES AGENCIES:

SIGNED BY _____ DATE _____

APPROVED AND SIGNED BY _____ DATE April 5, 1978

CHIEF OF SURVEY PARTY

MICHIGAN REGISTERED LAND SURVEYOR

Arthur O. Enger

Michigan Department of Natural Resources

SURVEYOR'S MICHIGAN REGISTRATION NO. 13581

