

# LAND CORNER RECORDATION CERTIFICATE

Authority: 1970 PA 74, MCL 54.205

Surveyor's Name: Stephan J. Szyszkoski

Field Survey Date: January 31, 2018

For corner(s) in: Iron County

## Original Public Land Survey Corner

## Corner Code

S          T          R           
S          T          R           
S          T          R           
S          T          R         

## Property Corner

## 1/16 Corner Code

a. S 26 T 44N R 34W 13 (GCDB 560220)  
b. S 26 T 44N R 34W 9 (GCDB 560240)  
S          T          R           
S          T          R         

1	A	B	C	D	E	F	G	H	I	J	K	L	M	1
2		6		5		4		3		2		1		2
3														3
4		7		8		9		10		11		12		4
5														5
6		18		17		16		15		14		13		6
7														7
8		19		20		21		22		23		24		8
9														9
10		30		29		28		27		26		25		10
11														11
12		31		32		33		34		35		36		12
13	A	B	C	D	E	F	G	H	I	J	K	L	M	13

## Part A. Corner History

a. Southeast 1/16 corner, Section 26. Not established in the original survey. Found no subsequent record.

b. Center-east 1/16 corner, Section 26. Not established in the original survey. Found no subsequent record.

## Part B: Surveyor's Report on Perpetuation, Restoration, Reestablishment, or Monumentation of Corner

a. Established the position for the corner at the intersection of straight lines connecting opposite 1/16 corners, those to the north, south, and west being monumented. From the position thus established, I found a 3/4" ID iron pipe, projecting 3 ft. above ground, bent, set by persons unknown, N85°W 24.2' distant, which I did not accept as marking the position for the corner.

b. Established the position for the corner midway and on a straight line between the Center of Section 26 1328.48' west and Quarter corner K10 1328.48' east. From the position thus established, I found a 2" brass Northern Paper Mills cap, no markings, affixed to a 1" ID iron pipe, N38°W 62.5' distant, which I did not accept as marking the position for the corner.

## Part C: Field Evidence of Perpetuation or Monumentation of Corner

a. Set 1"IDx28" I.pipe with 2" alum. MDNR cap.  
Set measuring nail with MDNR tag in the side of:  
4" Maple N15°W 15.0' mrkd "1/16S BT"  
5" Sugar N89°E 25.05' do  
6" Sugar S13°W 21.7' do  
4" Sugar S71°W 19.1' do  
Set sq'd cedar post adjacent.  
E= 7882806.92 N= 156091.92

b. Set 1"IDx28" I.pipe with 2" alum. MDNR cap.  
Set measuring nail with MDNR tag in the side of:  
10" Sugar N71°E 22.55' mrkd "1/16S BT"  
5" Sugar S35°E 10.1' do  
13" Sugar S80°W 22.8' do  
7" Sugar N63°W 23.3' do  
Set sq'd cedar post adjacent.  
E= 7882818.51 N= 156488.79

Bearings are magnetic. Coordinates are MCS83 in meters, NAD83(2011) Epoch 2010.00

Stephan J. Szyszkoski

02/26/2018

Professional Surveyor's License No.: 33986

page 1 of 1

Prepared By: S.J. Szyszkoski for the Michigan Dept. of Natural Resources, 427 N. US41 Baraga, MI 49908

