

MAR 09 2000

SECTION

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

For corners in

Iron
(County)

Located In:

Corner Code #

- | | | |
|------------------------------------|---|----------------|
| 1. Public Land Survey | T <u>44N</u> R <u>34W</u> | E-6.7
(001) |
| | T <u> </u> R <u> </u> | |
| | T <u> </u> R <u> </u> | |
| | T <u> </u> R <u> </u> | |
| 2. Property Controlling in Section | S <u> </u> T <u> </u> R <u> </u> | |
| | S <u> </u> T <u> </u> R <u> </u> | |
| 3. Miscellaneous | S <u> </u> T <u> </u> R <u> </u> | |
| Property in Sec. | S <u> </u> T <u> </u> R <u> </u> | |

IRON COUNTY
MICHIGAN
RECEIVED FOR RECORD

99 DEC 30 AM 10:10
L.C. Records: L. 8, P. 10

Gary L. Pisoni
REGISTERED LAND SURVEYOR

Register of Deeds Stamp & File Number

4. Lot No. , Recorded Plat
5. Private Claims

North Meander Corner Section 16 and 17, T44N, R34W

I, Gary L. Pisoni, in a field survey on March 10, 1999 do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and /or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2		6		5		4		3		2		1	
3													
4		7		8		9		10		11		12	
5													
6		18		17		16		15		14		13	
7													
8		19		20		21		22		23		24	
9													
10		30		29		28		27		26		25	
11													
12		31		32		33		34		35		36	
13													

A. Description of original monument and accessories and/or subsequent restoration:

Original corner established on August 15, 1851 by Guy H. Carleton, U.S. Deputy Surveyor.

Original Corner; Wood Post

Original Bearing Trees:

Cedar	12"	N 22°E	66 lks(43.56 feet)
Cedar	10"	N 28°W	59 lks(38.94feet)

PEER GROUP APPROVED 12-28-99
Iron Ray Pisoni
COUNTY REPRESENTATIVE

On 11-08-76, Arthur Enger, RLS, re-established corner on N. Bank of Paint River at record distance of 60.34 S. of post at Sec. Cor. 8, 9, 16, 17. Set a 1" diameter by 36" long iron pipe with a 3 3/4" aluminum cap, stamped as follows: T44N, R34W, S-17, S-16, M.C., 11/8/76, RLS 13581, recorded in Liber 1, Page 523 of L.C. records.

1976 Bearing Trees:

White Birch	3"	N 10°E	15.00 feet
Elm	8"	S 53°W	17.30 feet

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

On 3-10-99 found monument as described above and the remains of the above described bearing trees.

Corner is 6' from waters edge.

Corner record research on file with county representative.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

Blazed and scribed the following new bearing trees: (All measurements taken to a nail in side of tree)

Balsam	8"	S 48°W	16.20 feet
Balsam	7"	N 60°W	5.37 feet
Balsam	9"	N 29°W	15.63 feet
Steel sign post		N 05°W	0.70 feet

99-10
Signed by *Gary L. Pisoni* Date 12-28-99

Surveyor's Michigan License No. 27457

FORM APPROVED BY MICHIGAN STATE BOARD OF PROFESSIONAL SURVEYORS JAN. 28, 1971
REVISED MAY 14, 1975
REVISED JAN., 1983
REVISED OCT., 1995

LIBER

8 PAGE

10

