

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970 as Amended

For corners in

Iron (County) Located In: Corner Code #
1. Public Land Survey T R
2. Property Controlling in Section S 24 T 45N R 31W 8 (GCDB 620340)
3. Miscellaneous Property in Sec. S T R (GCDB 640320)
4. Lot No. , Recorded Plat
5. Private Claims

Register of Deeds Stamp & File Number

Table with 13 rows and 13 columns (A-M) for Register of Deeds Stamp & File Number.

I, Stephan J. Szyszkoski, in a field survey on 8 04/20/16 do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and /or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

(8-Sec. 24) Center-West 1/16 corner, Section 24. Not previously monumented.

(12-Sec. 24) Center-South 1/16 corner, Section 24. Not previously monumented.



B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

(8-Sec. 24) Established the position for the corner at the intersection of the E-W 1/4 line of Section 24 with the West 1/16 line of Section 24. The direction of the E-W 1/4 line is the weighted mean bearing of the north and south lines of the section. The West 1/16 line is a straight line between 1/16 corners #1 and #15.

(12-Sec. 24) Established the position for the corner midway and on a straight line between Quarter corner 1336.16' south and the intersection of 1/4 lines of Section 24 1336.16' north. The E-W 1/4 line of Section 24 is the weighted mean bearing of the north and south lines of the section.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

(8) Set 1"IDx28" I.pipe with 2" alum. MDNR cap. Set measuring nail with MDNR tag in the side of: 6" Cherry N60°E 30.7' mrkd "1/16S BT" 5" Cherry S80°E 25.05' do 5" Spruce S31°E 40.45' do 5" Balsam N76°W 29.9' do Set sq'd cedar post adjacent. E= 7912698.372 N= 167270.023

(12) Set 1"IDx28" I.pipe with 2" alum. MDNR cap. Set measuring nail with MDNR tag in the side of: 4" twin B.Spruce N34°W 9.0' mrkd "1/16S BT" 7" Balsam S68°E 39.25' do 3" Cherry S40°E 25.45' do 4" Balsam South 49.0' do E= 7913090.644 N= 166861.381

Bearings are magnetic. Coordinates are MCS83 in meters, NAD83(2011) Epoch 2010.00 datum. Coord. Ref.=NGS PID RL0202: N= 156159.364 m. E= 7917031.370 m.

Signed by [Signature] Date 04/25/2016
Surveyor's Michigan License No. 33986

For the Michigan Department of Natural Resources, Forest Resources Division