

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

For corners in

Iron

(County)

Located In:

Corner Code #

1. Public Land Survey

T 45N R 32W

E13

T R

T R

T R

2. Property Controlling
in Section

S 32

T 45N R 32W

4

S T R

3. Miscellaneous
Property in Sec.

S

T R

S

T R

Register of Deeds Stamp & File Number

4. Lot No. , Recorded Plat

5. Private Claims

Sep 25 2003

I, Stephan J. Szyszkoski, in a field survey on _____, 20____ do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law, established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

| | A | B | C | D | E | F | G | H | I | J | K | L | M |
|----|---|----|---|----|---|----|---|----|---|----|---|----|---|
| 1 | | | | | | | | | | | | | |
| 2 | | 6 | | 5 | | 4 | | 3 | | 2 | | 1 | |
| 3 | | | | | | | | | | | | | |
| 4 | | 7 | | 8 | | 9 | | 10 | | 11 | | 12 | |
| 5 | | | | | | | | | | | | | |
| 6 | | 18 | | 17 | | 16 | | 15 | | 14 | | 13 | |
| 7 | | | | | | | | | | | | | |
| 8 | | 19 | | 20 | | 21 | | 22 | | 23 | | 24 | |
| 9 | | | | | | | | | | | | | |
| 10 | | 30 | | 29 | | 28 | | 27 | | 26 | | 25 | |
| 11 | | | | | | | | | | | | | |
| 12 | | 31 | | 32 | | 33 | | 34 | | 35 | | 36 | |
| 13 | | | | | | | | | | | | | |

A. Description of original monument and accessories and/or subsequent restoration:
(E13) Corner common to Sections 32-33 T45N-R32W and 4-5 T44N-R32W. 1951: Monumented by Dean C. DeLaMater from two GLO bearing trees and the remains of what possibly was the original post. Set 1" pipe with 4" brass cap. 10" H. Maple N72W 34 links, 10" H. Maple N52E 56 links.

(4-Sec. 32) Northwest 1/16 corner, Section 32. Not established in the original survey.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

(E13) Recovered the monument in good condition and at record bearing and distance from the 1951 witness trees. The H. Maple NW is in good condition with overgrown blazes. The other NBT is now a rotting stump. The monument cap was found stamped incompletely: "32-33-4-5 32W". Left the monument in place and made new witnesses as described below.

(4-Sec. 32) Found no evidence of prior monumentation on the ground. Established the corner at the intersection of straight lines connecting opposite 1/16 corners.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

(E13) Found 1" ID I. pipe with 4" brass MI Dept. of Conservation cap. Blazed, scribed, and set meas. nails in:

20" Sugar N66W 22.6' *

8" Sugar N26E 13.2' "S33 NBT"

11" Y. Birch S37E 33.1' "S4 NBT"

10" Sugar S20E 13.0' "S4 NBT"

Bearings are magnetic. Distances are to nail with tag. * denotes 1951 NBT.

(4) Set 1" ID x 32" I. pipe with 4" alum.

MDNR cap. Blazed, scribed, and set

measuring nails in:

9" W. Spruce S62E 12.6' "1/16S BT"

9" W. Spruce S61W 19.2' do

4" Balsam N53W 0.65' do

9" W. Spruce N14E 23.7' do

Set squared spruce post adjacent.

Bearings are magnetic. Distances are to nail with tag.



Signed by

Stephan J. Szyszkoski

Date

9/30/03

Surveyor's Michigan License No.

33986

For the Michigan Department of Natural Resources - Office of Land and Facilities

FORM APPROVED BY MICHIGAN STATE BOARD OF PROFESSIONAL SURVEYORS, JAN. 28, 1971

REVISED MAY 14, 1975

REVISED JAN. 1983

REVISED OCT. 1995