

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970 as Amended

For corners in

Iron Located In: Corner Code #
1. Public Land Survey
2. Property Controlling in Section
3. Miscellaneous Property in Sec.
4. Lot No. , Recorded Plat
5. Private Claims

Register of Deeds Stamp & File Number

Table with 13 rows and 13 columns (A-M) for Register of Deeds Stamp & File Number.

I, Stephan J. Szyszkoski, in a field survey on 05/05/15 do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and /or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

(6-Sec. 34) Northeast 1/16 corner, Section 34. Not previously monumented.

(8-Sec. 34) Center-West 1/16 corner, Section 34. Not previously monumented.



B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

(6-Sec. 34) Established the position for the corner at the intersection of straight lines connecting opposite 1/16 corners.

(8-Sec. 34) Established the position for the corner midway and on a straight line between Quarter corner 1321.53' west and the Center of Section 34 1321.53' east.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

(6) Set 1"IDx28" I.pipe with 2" alum. MDNR cap. Set measuring nail with MDNR tag in the side of: 3" Balsam N16°E 6.2' mrkd "1/16S BT" 7" Balsam S25°E 8.1' do 10" Maple S67°W 15.4' do 5" Cherry N60°W 21.1' do Set sq'd cedar post adjacent. E= 7890999.896 N= 164773.705

(8) Set 1"IDx28" I.pipe with 2" alum. MDNR cap. Set measuring nail with MDNR tag in the side of: 8" Cedar S60°E 50.2' mrkd "1/16S BT" Set sq'd cedar post N36°W 0.9' to center South 0.3' edge of boulder 5' wide, 6' long 2.5' high. No other witnesses available. Hemlock River is 14' north. E= 7890185.525 N= 164385.949

Bearings are magnetic. Coordinates are MCS83 in meters, NAD83(2011) Epoch 2010.00 datum. Coord. Ref.=NGS PID AA8081: N= 147176.690 m. E= 7895147.466 m.

Signed by [Signature] Date 08/17/2015
Surveyor's Michigan License No. 33986

For the Michigan Department of Natural Resources, Forest Resources Division