

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970 as Amended

For corners in

Iron (County)	Located In:	Corner Code #
1. Public Land Survey	T R	
	T R	
	T R	
2. Property Controlling in Section	S 16 T 45N R 34W	11
	S 16 T 45N R 34W	9-13
		(SMC between
3. Miscellaneous Property in Sec.	S T R	Gov't Lots 4 & 5)
	S T R	
4. Lot No. , Recorded Plat		
5. Private Claims		

Register of Deeds Stamp & File Number

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2		6		5		4		3		2		1	
3													
4		7		8		9		10		11		12	
5													
6		18		17		16		15		14		13	
7													
8		19		20		21		22		23		24	
9													
10		30		29		28		27		26		25	
11													
12		31		32		33		34		35		36	
13													

I, Stephan J. Szyszkoski, in a field survey on SMC 12/06/12 do hereby state
that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2
above were in conformance with regulations and rules therefore as required in the current manual of survey
instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of
a Court of Law and /or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with
the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established,
re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded
on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

(11-Sec. 16) Southwest 1/16 corner, Section 16. Not previously monumented.

(SMC) Special Meander Corner between Government Lots 4 and 5, on the East 1/16 line of Section 16
between 1/16 corners #9 and #16. Not previously monumented.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

(11-Sec. 16) Established the position for the corner at the intersection of straight lines
connecting opposite 1/16 corners.

(SMC) Established a witness corner to the position for the corner on the north bank of the Net
River, on a straight line between 1/16 corner #9 1040.94' north and 1/16 corner #16, 1594.94' south.
The water's edge of the Net River is approx. 44' South of the corner position. The position is not
intended to mark the OHWM of the Net River.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

(11) Set 1"IDx32" I.pipe with 4" alum. MDNR cap.
Set measuring nail with MDNR tag in the side of:
8" twin Maple N04E 21.3' mrkd " X X "
11" W.Birch N61E 32.7' do
7" Spruce S28W 69.3' do
19" W.Pine N28W 41.3' do
Set sq'd Cedar post adjacent.
N=169075.451 E=7879037.976

(SMC) Set 1"IDx32" I.pipe with 4" alum. MDNR cap.
The cap is stamped to identify the position as
being a WC to the SE1/16 corner, which would be
277.00' south.
Set measuring nail with MDNR tag in the side of:
10" W.Birch N43E 7.6' mrkd "WC BT"
5" Balsam S52E 19.0' do
14" Spruce S57W 51.2' do
8" Maple S68W 39.9' do
Set sq'd Cedar post adjacent.
N=169155.576 E=7879842.880

Bearings are magnetic. Coordinates are MCS83, in meters

Signed by Stephan J. Szyszkoski
Surveyor's Michigan License No. 33986

Date 01/14/2013

For the Michigan Department of Natural Resources, Forest Resources Division

