

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970 as Amended

For corners in

| Iron | Located In: | Corner Code # |
|------------------------------------|-----------------|---------------|
| (County) | | |
| 1. Public Land Survey | T R | |
| | T R | |
| | T R | |
| 2. Property Controlling in Section | S 5 T 45N R 34W | 16 |
| | S T R | (GCDB 260600) |
| | S 5 T 45N R 34W | 13 |
| | S T R | (GCDB 260620) |
| 3. Miscellaneous Property in Sec. | S T R | |
| | S T R | |
| 4. Lot No. , Recorded Plat | | |
| 5. Private Claims | | |

Register of Deeds Stamp & File Number

| | A | B | C | D | E | F | G | H | I | J | K | L | M |
|----|----|---|---|----|---|----|---|----|---|----|---|----|---|
| 1 | | | | | | | | | | | | | |
| 2 | 6 | | | 5 | | 4 | | 3 | | 2 | | 1 | |
| 3 | | | | | | | | | | | | | |
| 4 | 7 | | | 8 | | 9 | | 10 | | 11 | | 12 | |
| 5 | | | | | | | | | | | | | |
| 6 | 10 | | | 17 | | 16 | | 15 | | 14 | | 13 | |
| 7 | | | | | | | | | | | | | |
| 8 | 19 | | | 20 | | 21 | | 22 | | 23 | | 24 | |
| 9 | | | | | | | | | | | | | |
| 10 | 30 | | | 29 | | 28 | | 27 | | 26 | | 25 | |
| 11 | | | | | | | | | | | | | |
| 12 | 31 | | | 32 | | 33 | | 34 | | 35 | | 36 | |
| 13 | | | | | | | | | | | | | |

I, Stephan J. Szyszkoski, in a field survey on 07/01/15 do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey Instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and /or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

(16-Sec. 5) East 1/16 corner between Section 5 and 8. Not previously monumented.

(13-Sec. 5) Southeast 1/16 corner, Section 5. Not previously monumented.



B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

(16-Sec. 5) Established the corner midway and on the Section line between Section corner 1313.79' east and Quarter corner 1313.79' west.

(13-Sec. 5) Established the corner at the intersection the East and South 1/16 lines of Section 5. The East 1/16 line is parallel to the weighted mean bearing of the N-S 1/4 line and that part of the East line of Section 5 south of Porter Lake. The South 1/16 line is parallel to the weighted mean bearing of the E-W 1/4 line and South line of Section 5.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

(16) Set 1"IDx28" I.pipe with 2" alum. MDNR cap.
Set measuring nail with MDNR tag in the side of:
10" Sugar N31°E 17.5' mrkd "1/16S BT"
6" Sugar S72°E 15.2' do
14" Sugar S66°W 16.35' do
12" Y.Birch N70°W 19.55' do
Set sq'd Cedar post adjacent.
E= 7878306.172 N= 171889.392

(13) Set 1"IDx28" I.pipe with 2" alum. MDNR cap.
Set measuring nail with MDNR tag in the side of:
10" Sugar N30°E 8.45' mrkd "1/16S BT"
10" Sugar S25°E 6.4' do
8" Sugar S68°W 21.5' do
8" Sugar N83°W 19.3' do
Set sq'd cedar post adjacent.
E= 7878311.247 N= 172287.774

Bearings are magnetic. Coordinates are MCS83 in meters, NAD83(2011) Epoch 2010.00 datum.
Coord. Ref.=NGS PID RL0476: N= 196482.411 m. E= 7879234.516 m.

Signed by Stephan J. Szyszkoski Date 09/15/2015
Surveyor's Michigan License No. 33986

For the Michigan Department of Natural Resources, Forest Resources Division