

SURVEY & REMONUMENTATION

FEB 21 2001

SECTION

LAND CORNER RECORDATION CERTIFICATE Filing Requirement of Act 74, Mich. P.A. 1970

For corners in

Iron
(County)

Located in:

Corner Code #

1. Public Land Survey

T 45N R 34W

C-13 ✓

T 44N R 34W

C-1

T R

T R

2. Property Controlling
in Section

S T

T R

S T

T R

3. Miscellaneous
Property in Sec.

S T

T R

S T

T R

COMMENCING YEAR 2000
RECEIVED FOR RECORD
IRON COUNTY, MICHIGAN

GO DEC -8 PM 1:02

L.C. Records: L. S. P. 249

Gilbert J. Pisoni
REGISTERED PROFESSIONAL SURVEYOR

Register of Deeds Stamp & File Number

4. Lot No. _____, Recorded Plat _____

5. Private Claims _____

Section Corner to Sections 31 and 32, T45N, R34W

Section Corner to Sections 5 and 6, T44N, R34W

I, Gary L. Pisoni, in a field survey on April 3, 2000, do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and /or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

Original corner established on September 15, 1846 by Austin Burt, U.S. Deputy Surveyor.

Original Corner; Spruce Post

Original Bearing Trees:

Spruce	7"	N 56° E	35 links (23.10 feet)
White Pine	16"	N 8 1/2° W	78 links (51.48 feet)

On August 18, 1851, Guy H. Carleton, U.S. Deputy Surveyor established the following new bearing trees:

White Birch	8"	S 06° W	28 links (18.48 feet)
White Birch	8"	S 80° E	26 links (17.16 feet)

On 8/15/72 Arthur O. Enger RLS DNR restored the corner position by proportionate measurement and set a 1" diameter by 36" long iron pipe with a 4" diameter aluminum cap stamped as follows: T45N, R34W, S-31, S-32, S-6, S-5, T44N, RLS 13581
Recorded in Liber 1, Page 269-270 of LC records.

1972 Bearing Trees:

Tamarack	11"	S 81 1/2° W	44.5 feet
Red Pine	20"	N 45° W	95.5 feet

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

No evidence of original B.T.s found.

On 4/13/200 found the above described monument and the following bearing trees:

Tamarack	15"	S 82° W	44.80 feet
Red Pine	22"	N 45° W	95.84 feet

Monument is 12" above ground surface.

Corner record research on file with County Representative.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

Blazed and scribed the following new bearing trees: (All measurements taken to a nail in side of tree)

Black Cherry	7"	N 65° E	38.30 feet
Popple	8"	S 65° E	44.12 feet
Steel sign post		South	0.95 feet

00-017

Signed by Gary L. Pisoni

Date 11-13-2000

Surveyor's Michigan License No. 27457

FORM APPROVED BY MICHIGAN STATE BOARD OF PROFESSIONAL SURVEYORS, JAN 28, 1971

