SURVEY & REMONUMENTATION

FEB 21 2001

SECTION

LAND CORNER RECORDATION CERTIFICATE Filling Requirement of Act 74, Mich. P.A. 1970

For comers in			
IRON (county)	Located In:	Corner Code#	COMMENCING YEAR 2000
BATES TOWNSHIP	T 46 N, R 35 W	/ D-11 (S 1/4 SEC.29)	RECEIVED FOR RECORD
1. Public Land Survey		<u></u>	controll, ANIO-09
2. Property controlling			L.C. Records: L. 8, P. 185
in Section	s		Tillen Milie
3. Miscellaneous Property in Sec.	s		ি কুল ক্ষাত্তি হ'ল হয়ে। Register of Deeds Stamp & File Number
		•	Register of Deeds Starrip & File Number
4. Lot No, Record 5. Private Claims	ed Plat		A B C D E F G H 1 J K L M
1/4 CORNER COMMO			2 -6 -5 -4 -3 -2 -1 -1
I, STEVEN R. APPLEKAMP	in a field survey on NOVEM	IBER 9, 2000 do hereby stat	te that under 4 7 8 9 9 10 11 12
requirements of P.A. 74, Michigan I conformance with regulations and r of the United States Department of	ules therefore as required in the	e current manual of survey insti	ructions 5
and/or that the corner points mention Michigan Board of Land Surveyors	ned in lines 3,4 and 5 above we	ere in conformance with the rule	unt of law 6 18 17 16 15 14 13 es of the 7
monumented, recovered, found as	•		8 -19 -20 -21 -22 -23 -24
NOTE: Not more than 2 corn on this certificate.	ers, all in the same town an	d range, may be recorded	9 10 30 29 28 27 26 25
			11
A. Description of original mon	ument and accessories and	d/or subsequent restoration	
ORIGINAL CORNER ESTAB JUNE 12, 1851.	LISHED BY HARVEY MELLE	N, U.S. DEPUTY SURVEYOR	ON 13
ORIGINAL BEARING TREES	16" 16"		PEER GROUP APPROVED FROM Alay & From 11-30-2000 FROM Alay & PEOPLE ENTATIVE
	\$ 51°E \$ 61°W 11 LINKS 14 LINKS		COUNTY REPRESENTATIVE
THE TWO ORIGINAL STAMPED AS FOLL	L BEARING TREES, HE SET.	A 2" I.D. BY 5 FEET LONG (ENCE WHICH INCLUDED THE REMAINS OF GALVANIZED IRON PIPE WITH 3" BRONZE TABLET RECORDED IN LIBER 3 PAGE 206 OF L.C. RECORDS.
SUGAR	Y-BIRCH SUGAR	SUGAR	IN 1982 GARY PISONI AND MARK SELMO ADDED ONE BEARING TREE BECAUSE
9" N 58°W 38.8'	10" 5" S 14°E S 45°W 32.8' 21.9'	S 22°E 35.49°	THE Y-BIRCH FROM 1968 IS NOW DEAD.
B. Description of corner evid		applied in restoring or rees	stablishing corner:
FOUND CORNER IN RECORD, ACCEPTE	GOOD CONDITION AS REC	ORDED IN 1968 AS PER LAN MATCHED THE BEARING T	REES FOUND.
EXISTING	EXISTING EXISTING		PROFESSIONAL SURVEYOR NO. 43045
SUGAR 15" S 18°E	SUGAR SUGAR 8" 13" S 50°W N 58°W		43045
35.44	21.99' 38.85'	•	- CESSIQNI
		• •	ocating the position of the corner:
STAMPED AND IN THE	ORIGINAL POSITION PER TI	ALV. PIPE APPROX. 1.5 AB(HE 1968 LAND CORNER RE(NCES. (ALL MEASUREMENT	
SUGAR	Y-BIRCH STEEL SIGN		
5" N 72°E 18.54'	8" POST N 04"W NE 40.95' 0.77'		
	^		
\wedge	40/10	_	NOVEMBER 9, 2000
Signed by	un D. Pople	~	Date NOVEMBER 9, 2000
Surveyor's Michigan License	No. 43045	4	