



8 0 4 1 5 4 1

Tx:4028993

2/11/2015 4:45:00 PM

LAND CORNER RECORDATION CERTIFICATE

Filing Requirement of Act 74, Mich. PA 1970

For Corners In:

Kalkaska

(County)

Located In

Corner Code #

1. Public Land Survey

T

R

T

R

2. Property Controlling
in Section

S

36

T

25N

R

7W

11

S

36

T

25N

R

7W

12

3. Miscellaneous

Property in Section

S

T

R

S

T

R

4. Lot No:

Recorded Plat:

5. Private Claims:

I, Joshua R. Davidson, in a field survey on June 5, 2014 do hereby state that under requirements of PA 74, Michigan PA of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

DOCUMENT #

3123278

JOANN DEGRAAF

KALKASKA CTY ROD

KALKASKA, MI

RECORDED ON

02/12/2015 2:05 PM

REC FEE: 14.00

PAGES: 1

BK: 3PG: 401

Register of Deeds Stamp & File Number

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2		6		5		4		3		2		1	
3													
4		7		8		9		10		11		12	
5													
6		18		17		16		15		14		13	
7													
8		19		20		21		22		23		24	
9													
10		30		29		28		27		26		25	
11													
12		31		32		33		34		35		36	
13													

A. Description of original monument and accessories and/or subsequent restoration:

11 – SW 1/16 corner section 36

12 – CS 1/16 corner section 36

None

None

B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:

11 – SW 1/16 corner section 36

12 – CS 1/16 corner section 36

Set a stamped 2" aluminum cap on a 5/8" x 34" rebar per standard BLM procedure.

Set a stamped 2" aluminum cap on a 5/8" x 34" rebar per standard BLM procedure.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

11 – a stamped 2" aluminum cap on 5/8" x 34" rebar

12 – a stamped 2" aluminum cap on 5/8" x 34" rebar

N78°E 12.70' to set nail & tag in S. side 10" W. Pine
S13°E 72.02' to set nail & tag in E. side 11" R. Pine
S43°W 61.71' to set nail & tag in SE. side 13" R. Pine
N24°W 133.81' to set nail & tag in W. side 30" Oak
Set blue post with location tag 1' Southwest

N80°E 40.85' to set nail & tag in N. side 15" Cedar
S41°E 14.57' to set nail & tag in SW. side twin 10" Cedar
N80°W 13.70' to set nail & tag in N. side 5" R. Maple
N08°W 59.38' to set nail & tag in E. side 12" Cedar
Set blue post with location tag 1' Northeast

Signed by:

Joshua R. Davidson

Date:

2-11-15

Surveyor's Michigan License No.:

46659

