

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

MAR 1 2000

For corners in

KALKASKA
(County)

Located In:

Corner Code #

SECTION

1999 REMONUMENTATION

1. Public Land Survey

T 25N R 8W

L-9

2. Property Controlling
in Section

S T R
S T R

3. Miscellaneous
Property in Sec.

S T R
S T R



3020144

Page: 1 of 1
02/04/2000 03:49P
RENON
LB: B PG: 98

Kalkaska County Jean Hall, Register

Register of Deeds Stamp & File Number

4. Lot No. _____, Recorded Plat _____

5. Private Claims _____

I, EUGENE FARRIER, in a field survey on November 9, 1999 do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and for that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2		5		5		4		3		2		1	
3													
4		7		8		9		10		11		12	
5													
6		18		17		16		15		14		13	
7													
8		19		20		21		22		23		24	
9													
10		30		29		28		27		26		25	
11													
12		31		32		33		34		35		36	
13													

A. Description of original monument and accessories and/or subsequent restoration:

L-9: 1/4 Cor. Common to Sec. 24 & 25, T25N-R8W, Springfield Township

1853, G.L.O. Resurvey, by V.W. Caukin (Deputy Surveyor) Co. Survey Notes Pg 317, Sugar 18", S5°E, 13 Lks; Beech 14", North 22 Lks
1912, Fargo Survey, found old stake in road East and West and roots of 2 U.S. witness trees

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

L-9: 1/4 Cor. Common to Sec. 24 & 25, T25N-R8W, Springfield Township

Set 5/8" X 18" rerod w/brass cap in mon. box 2' North of centerline E-W road & 2' East of fence to North, midway & on line btw SW & SE Section cor.
South 32.40', triangular concrete marker
S25°W, 28.12', power pole, set nail & washer
N13°W, 32.90', power pole, set nail & washer
N35°E, 37.25', 12" Oak, set nail & washer
S49°32'26"W, 4.65', found spike
No G.L.O. witnesses were found.

Ratified by Peer Group
P.A. 345 - 1990 Kalkaska County

Chairman Eugene Farrier

Date 02-03-00



C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

L-9: 1/4 Cor. Common to Sec. 24 & 25, T25N-R8W, Springfield Township

Set 5/8" X 18" rerod w/brass cap in mon. box
South 32.40', triangular concrete marker
S25°W, 28.12', power pole, set nail & washer
N13°W, 32.90', power pole, set nail & washer
N35°E, 37.25', 12" Oak, set nail & washer
S49°32'26"W, 4.65', found spike

Kalkaska County Peer Group accepted the above monument as a careful and faithful reestablishment of the position of the original corner.

Signed by Eugene Farrier
Michigan License No. 24594

Date 02-04-00 Surveyor's