

LAND CORNER RECORDATION CERTIFICATE

Filing Requirement of Act 74, Mich. PA 1970

For Corners In:

Kalkaska
(County)

Located In

Corner Code #

- | | | | | |
|--------------------------------------|------|-------|------|---|
| 1. Public Land Survey | T | | R | |
| | T | | R | |
| 2. Property Controlling in Section | S 27 | T 26N | R 5W | 1 |
| | S 27 | T 26N | R 5W | 4 |
| 3. Miscellaneous Property in Section | S | T | R | |
| | S | T | R | |

4. Lot No: Recorded Plat:

5. Private Claims:

I, Craig W. McVean, in a field survey on October 26, 2010 do hereby state that under requirements of PA 74, Michigan PA of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

Register of Deeds Stamp & File Number

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2	6		5		4		3		2		1		
3													
4	7		8		9		10		11		12		
5													
6	18		17		16		15		14		13		
7													
8	19		20		21		22		23		24		
9													
10	30		29		28		27		26		25		
11													
12	31		32		33		34		35		36		
13													

A. Description of original monument and accessories and/or subsequent restoration:

1 - None

4 - None



B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:

1 - West 1/16 corner common to section 22 and 27, T26N, R5W - Found no evidence of a corner. Area recently burned over. Set 2" Aluminum Cap on 5/8" x 34" rebar per Standard BLM procedure.

4 - Northwest 1/16 corner of section 27 - Found no evidence of a corner. Set 2" Aluminum cap on 5/8" x 34" rebar per Standard BLM procedure. CL 2-track is 31' N.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

1 - Stamped 2" Aluminum Cap on 5/8" x 34" rebar

N44°E 57.75' to set 3/4" X 18" rebar
S67°E 53.16' to set 1/2" X 18" smooth iron bar
S40°W 48.19' to set 5/8" X 18" rebar
N68°W 66.57' to set 1/2" X 24" smooth iron bar
Set Blue Carsonite Post with location tag 1' Northeast

4 - Stamped 2" Aluminum cap on 5/8" x 34" rebar

N82°E 133.70' to set Nail & Tag in S. side 10" Cherry
S78°E 157.35' to set Nail & Tag in S side 6" & 10" tw. Cherry
S72°W 57.72' to set Nail & Tag in S. side 9" Cherry
N45°W 73.88' to set Nail & Tag in NE. side 13" Cherry
Set Blue Carsonite Post with location tag 1' Southeast

Signed by:

Craig W. McVean

Date:

1/20/2011

Surveyor's Michigan License No.:

39088