

LAND CORNER RECORDATION CERTIFICATE
FILING REQUIREMENT OF ACT 74, MICH. P.A.1970

FOR CORNERS OF--:	LOCATED IN--:	CORNER CODE NUMBER
1. PUBLIC LAND SURVEY_____ T. _____ N. _____ E. _____ S., R. _____ W. _____		
2. PROPERTY CONTROLL- ING IN SECTION 21, T. 27 N. 5 W. ●		10; 11; 15
3. MISCELLANEOUS PROPERTY IN SECTION _____, T. _____ N. _____ E. _____ S., R. _____ W. _____		
4. LOT NO. _____, RECORDED PLAT _____		
5. PRIVATE CLAIMS _____		

REGISTER OF DEEDS STAMP AND
FILING NUMBER

I, Carl F. Roser, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were, in a field survey on March 10, 1976, established, re-established, monumented, re-monumented, recovered or restored as expressed below and in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a court of law. Furthermore, that the corner points mentioned in lines 3, 4 and 5 above were, in a field survey on _____, 19____, found, recovered, restored, established or re-established as expressed below and in conformance with the rules of the Michigan State Board of Registration for Land Surveyors or, by a Decree of a Court of law:

A. Description of original monument and accessories and/or subsequent restoration:

B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:

- 0 10 Established 1/16 corner equidistant and on line between found section corner south and found 1/4 corner north.
- 1 // Established center of SW 1/4 of Sec. 21 per standard B.L.M. instructions.
- 5 15 Established 1/16 corner per standard B.L.M. instructions.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

10	11	15
Drove 3/4" x 18" Iron	Set 1 1/4"x36" Pipe & cedar	Set 1 1/4"x36" Pipe - cedar post
4" R. Pine N51°E 42.28	post w/loc. tag	9" R. Pine S38°W 76.3
5" R. Pine S35°E 48.28	9" B.Cherry S34°W 69.4	7" R. Pine N02°W 62.2
6" R. Pine S71°E 33.50	11" Maple N89°E 45.6	36" W.Pine Stp. N86°E 52.5
	5" W. Pine N08°W 48.70	E-W Dirt Trail Due N 90'±
	Fd. 1" pipe N09°W 3.80	

SIGNED BY Carl F. Roser 4-28-77 DATE _____

SURVEYOR'S MICHIGAN REGISTRATION NO. 12028

FOR STATE AND UNITED STATES AGENCIES:

SIGNED BY _____ DATE _____

CHIEF OF SURVEY PARTY

APPROVED AND SIGNED BY _____ DATE _____

MICHIGAN REGISTERED LAND SURVEYOR

(SEAL)

SURVEYOR'S MICHIGAN REGISTRATION NO. _____

BEAR LAKE TOWNSHIP
KALKASKA COUNTY

FORM APPROVED BY MICHIGAN STATE BOARD OF REGISTRATION, JAN. 28, 1971
REVISED MAY 14, 1975

MAY PLACE SKETCH ON BACK OR ATTACHED SHEET

SURVEYOR'S MICHIGAN REGISTRATION NO. _____ KALKASKA COUNTY

FORM APPROVED BY MICHIGAN STATE BOARD OF REGISTRATION, JAN. 28, 1971
REVISED MAY 14, 1975

MAY PLACE SKETCH ON BACK OR ATTACHED SHEET