For corners in	LAND CORNER Filing Require	RECORDATION CERTIFICA ment of Act 74, Mich. P.A. 19	TE SURVEY & TO REMONUMENTATION	
	anatad Inc	0	FEB 26 2001	
2000 REMONUMENTATION 1. Public Land Survey	27N R 7W 27N R 8W	Corner Code #	SECTION	
2. Property Controlling S T I I Section S T I S	RR			
4. Lot No, Recorded Plat _				
5. Private Claims	·		ABCDEFGHIJK	L
			3	i
I, <u>EUGENE FARRIER</u> , in a field statunder requirements of P.A. 74, Michiga and 2 above were in conformance with regmanual of survey instructions of the Unite Management or by a decree of a Court of La and 5 above were in conformance with the Decree of a Court of Law; established, re-estables.	in P.A. of 1970, the ci gulations and rules the od States Department ow and for that the corr rules of the Michigan	orner points mentioned in lines 1 refore as required in the current of the Interior, Bureau of Land ner points mentioned in lines 3, 4 Board of Land Surveyors or by a	8 19 20 21 22 23 9 10 30 29 28 27 26	-1: -1: -2:
NOTE: Not more than 2 comers, all in the son this cartificate.	same town and range,	may be recorded	11 29 28 27 26 11	_ _
on use countries.			12 31 32 33 34 35	3i
A. Description of original monument an A-3: Sec. Cor. Common to Secs. 6 & 7. T27N-R8W. Kalkaska Twp 1850, G.L.O. Resurvey, by Lucius Lyon, set Lks; Tamarack 10°, N63°E, 47 Lke 1888, Survey, by E. Mosher (Co. Surveyor) f 1902, Survey, by Merrill (Co. Surveyor), Bk. 2 1922, Survey, by W.S. Merrill (Co. Surveyor), 1967, Survey for Consumers Power Co. by & 1974, Survey, by J.L. Wilcox, Liber 1, pg 82 S45°E, 17.25° 1988, Survey, by N. DeYoung, not recorded, N05°E, 33.10° 1994, Survey, by N.L. Way, not recorded, fo Maple 8°, N50°W, 20.60°	T27N-R7W, Kalkasi Cedar post for corner, or road, measured fron 21, Pg 64, shows corn 1, Bk 28, Pg 52, Cedar Aary Feindt, calcutated 4, found %" iron road found %" rod & R.L.S	sa Twp: M-3: Secs. 1 & 12. Temerack 9", N27°W, 16 Lks; Whin corner, no description or accessorer but no description or accessorer but no description or accessories stake & old government bearing tre location only at corner, Poplar 12", S70°W, 26. . cap #14102 at corner; Cedar 8",	te Pine 8", S33°W, 9 Lks; Cedar 8", S50°E ies es .32'; Popler 10", N10°E, 25.82'; W. Pine 4' West 1380'; Ceder 6", Eest 39.90'; Cedar 8	'", B",
B. Description of corner evidence found and A-3: Sec. Cor. Common to Secs. 6 & 7. Found & " iron & cap #14102 at corner, Wes S37°E, 21.93', 10" Cedar stump, found nail No G.L.O. witnesses were found.	T27N-R7W. Kalkasi at of West edge Rapid i	ca Twp: M-3: Secs. 1 & 12, T2		
C. Description of monument for corner and A-3: Sec. Cor. Common to Secs. 6 & 7. Found '%" Iron & cap #14102 at corner, Wes Set 5/8" X 30" iron rod & Co re-mon cap S37°E, 21.93', 10" Cedar stump, found nail N25°W, 18.89', 11" Cedar, set nail & wesher S89°E, 28.14', 4" Cedar, set nail & washer S89°E, 28.14', 4" Cedar, set nail & washer East 42' West edge of river	T27N-R7W. Kaikasi It of West edge Repid I	(a Twp: M-3: Secs. 1 & 12, T2)	7N-RBW. Kalkaska Two Coynty	Mag.

FARRIER POFESSIONA SURVEYOR

3026851 Page: 1 of 1 02/16/2001 10:26P REMON LB: 6 PG: 180

Kalkaska County Peer Group accepted the above monument as the best available evidence of the position of the original corner.