		R RECORDATION CERTIFIC ement of Act 74, Mich. P.A. 1	
For corners in  KALKASKA	Located In:	Corner Code #	SURVEY & REMONUMENTATION
2000 REMONUMENTATION  1. Public Land Survey	T <u>27N</u> R <u>7W</u> TR		FEB 26 2001
2. Property Controlling S	TR TR TR TR TR		SECTION
4. Lot No, Recorded P	lat		
5. Private Claims			A B C D E F G H I J K L
I, EUGENE FARRIER , in a state that under requirements of P.A. lines 1 and 2 above were in conforma current manual of survey instructions of Management or by a decree of a Court and 5 above were in conformance with Decree of a Court of Law; established, below:	74, Michigan P.A. of 197 ince with regulations and the United States Departr of Law and /or that the co the rules of the Michigan	rules therefore as required in the ment of the Interior, Bureau of Land orner points mentioned in lines 3, 4 n Board of Land Surveyors or by a	6 18 17 16 15 14 13 7 8 19 20 21 22 23 24
NOTE: Not more than 2 comers, all in on this certificate.	the same town and range	e, may be recorded	11
1974, Survey, by F. Arleth, Liber 1, Pg 1 44,90° 1981, Survey, by E. Ferrier (Co. Surveyo 1985, Survey, by E. Ferrier (Co. Surveyor 1990, LCRC, by E. Ferrier (Co. Surveyor 1994, Survey, by E. Ferrier (Co. Surveyor 44.98° (R. N60°W, 44.90°); set neil in V	a. 8. T27N-R7W. Kalkasi set Hemlock post; Hemlo o. Surveyor) for road, Co. 554, found 1/2" bar at co. or), recorded in Liber 2, Pg or), not recorded, corner & ), Liber 2, Pg 413 or), found iron & cap #594 W. Pine 12", S50°W, 9.9 oorded, found 1/2" bar at	ka Two ka Two ka 20", N27°W, 24 Lks; Hemlock Bk Pg 42 & Field Bk 4, Pg 53, mea rner; Maple 16", N22°E, 85.87'; W g 651, corner & accessories are the k accessories are the same as 1974 12 at comer; set nail W. Pine 6", N 1'; set nail in W. Pine 27", S45°E, corner; Maple 16", N22°E, 85.68'	l survey above 55°E, 72.44'; set nail in R. Pine 14", N65°W,
B. Description of corner evidence found C-4: 1/4 Cor. Common to Secs. 7 & Found 5/8" iron & cap #5942, 5' West on G.L.O. witnesses were found.	8. T27N-R7W. Kalkasi	ka Twp	
C. Description of monument for corner G-4: 1/4 Cor. Common to Secs. 7 & Found 5/8" iron & cap #5942, 5' West of Added Co. Re-mon aluminum cap. N65°K, 44.92', 18" R. Pine, set nail & N55°E, 72.45', 8" W. Pine, set nail & W575°E, 40.32', 10" W. Pine, set nail & S25°W, 45.82', 6" Oak, set nail & was Kalkaska County Peer Group accepted the	8. T27N-R7W. Kalkasi of centerline of road and in washer vasher washer her	ka.Twp n senterline trail road to East.	
Ratified by Peer Group P.A. 345 - 1990 Kalka Chairman Date	ska County		EUGENE D. * FARRIER PROFESSIONAL SURVEYOR No. 24594
Signed by Surveyor's Michigan License No. 2455	tamo	Date	Z-15-0/ MATOFESSIONALINA

3026861
Page: 1 of 1
27/15/2001 18:250
Kalkaska County Joan Hall, Register
LB: 6 PG: 190

PORM APPROVED BY MICHIGAN STATE BOARD OF PROFESSIONAL SURVEYORS, JAN. 28, 1971 PRIVAGED MAY 14, 1975 PRIVAGED JAN., 1985 REVISED DCT., 1885