

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

For corners in

**SURVEY &
 REMONIMENTATION**

FEB 26 2001

SECTION

<u>KALKASKA</u>	Located In:	Corner Code #
(County)		
2000 REMONUMENTATION		
1. Public Land Survey	T. <u>27N</u> R. <u>7W</u>	<u>G-2</u>
	T. <u> </u> R. <u> </u>	<u> </u>
	T. <u> </u> R. <u> </u>	<u> </u>
	T. <u> </u> R. <u> </u>	<u> </u>
2. Property Controlling	S. <u> </u> T. <u> </u> R. <u> </u>	<u> </u>
in Section	S. <u> </u> T. <u> </u> R. <u> </u>	<u> </u>
3. Miscellaneous	S. <u> </u> T. <u> </u> R. <u> </u>	<u> </u>
Property in Sec.	S. <u> </u> T. <u> </u> R. <u> </u>	<u> </u>
4. Lot No. <u> </u> , Recorded Plat <u> </u>		
5. Private Claims <u> </u>		

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2	6	5	4	3	2	1							
3													
4	7	8	9	10	11	12							
5													
6	18	17	16	15	14	13							
7													
8	19	20	21	22	23	24							
9													
10	30	29	28	27	26	25							
11													
12	31	32	33	34	35	36							
13													

I, EUGENE FARRIER, in a field survey on December 18, 2000 do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

G-2: 1/4 Cor. Common to Secs. 3 & 4, T27N-R7W, Kalkaska Twp

1850, G.L.O. Resurvey, by Lucius Lyon, set Beech post for 1/4 corner; Beech 12", S76°E, 29 Lks; Beech 8", N71°W, 9 Lks

1973, LCRC, by L.M. Gerschbacher, Liber 1, Pg 241, found 1.5" iron pipe with a 1/2" rebar in side (RLS cap #14102); R. Pine stump 36", West, 81.7'

1984, Survey, by E. Farrier (Co Surveyor) Liber 2, Pg 891, same as 1973 LCRC above

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

G-2: 1/4 Cor. Common to Secs. 3 & 4, T27N-R7W, Kalkaska Twp

Found 1/2" iron rod at corner in open field, confirmed location of corner to be the same as LCRC above, with a traverse into the corner. Added 5/8" X 18" rerod with aluminum cap.

S89°W, 115.66', 12" W. Pine, found nail

No G.L.O. witnesses were found.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

G-2: 1/4 Cor. Common to Secs. 3 & 4, T27N-R7W, Kalkaska Twp

Found 1/2" iron rod at corner in open field, confirmed location of corner to be the same as LCRC above, with a traverse into the corner. Added 5/8" X 18" rerod with aluminum cap.

S45°E, 40.79', 6" Cherry, set nail & tag

S14°W, 21.36', 4" Poplar, set nail & tag

S89°W, 115.66', 12" W. Pine, found nail, set nail & tag

N53°W, 152.04', 8" W. Pine, set nail & tag


Kalkaska County Peer Group accepted the above monument as the best available evidence of the position of the original corner.

Ratified by Peer Group

P.A. 345 - 1990 Kalkaska County

Chairman Eugene Farrier

Date 02-14-01



Signed by Eugene Farrier

Surveyor's Michigan License No. 24594

Date 2-15-01



Kalkaska County Joan Hall, Register

3026877

Page: 1 of 1

02/18/2001 10:28A

REMON

LB: 6 PG: 208

D OF PROFESSIONAL SURVEYORS, JAN. 28, 1971

REVISED MAY 14, 1976

REVISED JAN., 1983

REVISED OCT., 1996