## LAND CORNER RECORDATION CERTIFICATE Filing Requirement of Act 74, Mich. P.A. 1970

For corners in	<b></b>	The state of the s	. 1010	-
KALKASKA (County)	Located In:	Corner Code #	SUR\ REMONUN	/EY & MENTATION
2000 REMONUMENTATION  1. Public Land Survey	T_27N R_7W_ TR		FEB 2	6 2001
2. Property Controlling S in Section S  3. Miscellaneous S Property in Sec. S	TR TR TR TR TR		SECT	ION
4. Lot No, Recorded Pla	t	<u> </u>	_	
I, EUGENE FARRIER, in a field survequirements of P.A. 74, Michigan P.A. of were in conformance with regulations and instructions of the United States Depart decree of a Court of Law and for that the	rey on <u>December 11</u> 1970, the corner poin rules therefore as requ nent of the Interior, Bu	, 20 <u>00</u> do hereby state that und is mentioned in lines 1 and 2 abov ired in the current manual of surve ireau of Land Management or by	ve 6 -18 -17 -16-	G H I J K I M  3 2 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1
conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:  NOTE: Not more than 2 comers, all in the same town and range, may be recorded			of 8 19 20 21 9 10 30 29 28	27 26 25
on this certificate.		, may 20 1000 002	11 32 33	34 35 36
A. Description of original monument I-5: Sec. Cor. Common to Secs. 10. 1 1850: GLO Resurvey by Lucius Lyon; set I 30 links; Maple 14°, S 32°W, 27 links.	1. 14 & 15, T27N-R	7W. Kalkaska Two	131	<u></u>
1972: LCRC by C.E. Ostling in Liber 1 Pag at corner; T-pole, S 07°36'E, 47.31'; P.K.	e 97, LCRC by C.E. Os in road surface, N 0°1	tling in Liber 1 Page 152, Survey O'W, 10.0'.	by C.E. Oatling in Liber 1 Page	246; found 1 1/4" pipe
1973-1974; Survey by J.H. Granger in Lib 1 Pages 604-605; all found 2" pipe at corr	er 1 Page 801, LCRC b her; power pole, S 85°	y J.H. Granger in Liber 1 Page 29 E. 47.3'; Guard post, S 60°W, 59	9, and survey J.L. Fletcher, C 5.6'; Guard post, N 60°W, 58	ounty Surveyor, in Liber .9'.
1975: Survey (not recorded) by G.F. DeLeMater, found iron at corner; power pole, S 5°E, 47.38'; Triple cherry, S 40°E, 123.30',				
1977: Survey by J.L. Fletcher (Co. Surveyor), Liber 2 Page 51; same as 1973-1974 surveys above.				
1980: Survey for MDNR (not recorded) by	C.F. Roser; found 1 1/	2" pipe in menument box at corne	er. Note: fit witnesses by C.E.	Ostling and Granger
1993: Survey for County Road 612; found monument box at corner; iron, N 50'; power pole S 10°E, 47.62'; Stake, N 59°E, 64.31'.				
1993: ŁCRC by J.D. Geers in Liber 3 Page Power pole, S 03°E, 47.65'; 8" J. Pine, N	36; found 1 1/4" pipe 05°E, 108.65'; 6" Ch	of record in monument box in oer erry, S 16°W, 80.75'; 7 Cherry,	nterline County Road 612; Pow S 40°E, 123.20'.	ver pole N 65°E, 86.77';
8. Description of corner evidence found a L-5: Sec. Cor. Common to Secs. 10. 1 Found iron and cap # 14102 in monument Cherry, S 40°E, 123.01'; found neil in E el	1, 14 & 15, T27N-R	7W. Kalkaska Two y 812; found nait in NE side powe : 47.52'. <b>Ratified by Pe</b>		spike in W side 7"
No G.L.O. witnesses were found,		Chairman 2		MICHIGAN
C. Description of monument for corner a 1-5: Sec. Cor. Common to Secs. 10. 1 Found fron and cap #14102 in monument to 60°W, 134.10°, N side 8" R. Pine, set n N 73°E, 86.72°, NE side power pole, found \$ 40°E, 123.01°, W side 7" Cherry, found \$ 07°E, 47.52°, E side power pole, found	1. 14 & 15. T27N-R pox centerline Highway ail & tag d nail spike	7W. Kalkaska Two	rod and brass remon cap.	EUGENE D. FARRIER PROFESSIONAL SURVEYOR NO. 24594
Kalkaska County Peer Group accepted the	above monument as th	e best available evidence of the p	osition of the original corner.	WANTESSION NO.
٠	<i>CJ</i>	•	<u> </u>	
Signed by Comment	anies	Dat	2-15-01	
Surveyor's Michigan License No. 24594  Kalkaska County Joan Hall,	302 Page: 02/18/ REMON LB: 6	5889 FORM APPROVEDS 1 of 1 2001 10:25A PG: 218	Y MECHIGAN STATE BOARD OF PROFESS	ONAL SURVEYORS, JAN. 28, 1971 REVISED MAY 14,1975 REVISED OCT., 1986 REVISED OCT., 1986