SURVEY & REMONUMENTATION

LAND CORNER RECORDATION CERTIFICATE Filing Requirement of Act 74, Mich. P.A. 1970

Enr corners in

FEB 2 6 2001

rui comers in				
KALKASKA	Located In:	Corner Code #	AFATIAN	
(County) 2000 REMONUMENTATION		,	SECTION	
1. Public Land Survey	T_27N R_7W	M-6 1		
	T 27N R 6W	A-6		
	TR			
	<u>TR</u>			
• • • • • • • • • • • • • • • • • • • •	- <u>T</u> R			
in Section S 3. Miscellaneous S	TR TR			
Property in Sec. S	TR			
4. Lot No, Recorded Pl	at			
5. Private Claims	•		ABCDEFGHI	јк ј м
5. Private Claims				
			2 6 5 4 3	j — j — j
		00 de beerby steer state	4 7 8 9 10 10	1
I, <u>FUGENE FARRIER</u> , in a field requirements of P.A. 74, Michigan P.A.			ove	
were in conformance with regulations and rules therefore as required in the current manual of survey			vey 6 18 17 1-15 15-1-1	413
instructions of the United States Depar decree of a Court of Law and /or that th				
conformance with the rules of the Mich				3 24
Law; established, re-established, monum	ented, recovered, found as a	xpressed below:	9	┝╌┼╌┠╼┤
NOTE: Not more than 2 comers, all in	the same town and range, m	nay be recorded	10 30 29 23 27 27	625
on this certificate.	•	•	11-1-1-1-1-1-1-1-1-1-1-1-1-1-1-1-1-1-1-1	-
			12 31 32 33 34 3	536
A Managington of adiabat assessment			13	للللا
A. Description of original monument M-6: 1/4 Cor. Common to Sec. 13.			W.	
Excelsior Twp.	<u> </u>			•
1839; GLO survey by James H. Mullett; Sugar 10°, N 30°W, 12 links.	set 1/4 comer post at corne	r; Sugar 18", S 77°W, 18 lir	nks;	
-	and to Deale - Deale 00 0 0	• A		
• •	-		ness trees; (new) Beach 11", N 62°E, 21 lini	(s_
1900; Survey by W.S. Merrill, (Co. Surveyor), in Old Liber 1 Page 27; etone corner, found original bearing trees of government survey.				
1974: LCRC by D.E. Porter in Liber 1 Ps ₁ 17" Bass, S 60°W, 41.55'; 13" Maple,		corner, by single proportion,	fall in East shoulder of road; 9" Maple, N 75°	'W, 39.78';
1975 & 1977: Surveys by A.L. Dragoo in Liber 1 Page 770 and Liber 2 Page 199; found iron rod at corner.				
1975; LCRC by J.L. Wilcox in Liber 1 Page 383; found iron rod and cap #15410 at corner; 7" Maple, N B5°W, 39.84'; 14" Maple, S 70°W, 41.60'; 3" Elm, S 75°E, 15.48'.				
1989 & 1998: Surveys (not recorded) by N.B. DeYoung and by R. J. Kral, both found 1/2" rod at corner; 12" Maple, N 55°E, 47.30'; 3" Elm, N 48°E, 12.85'; 3" Elm, S 42°E, 21.30'; 1/2" rod, West 33.00'.				
1993; Survey (not recorded) by E. Farrier, (Co. Surveyor); found 1/2" iron w/partiel cap at corner; 10' East of centerline road; nell in 5" Elm, N 45°E, 13.05'; nell in 5" Elm, S 27°E, 21.54'; nell in 3° Elm, N 23°E, 25.28'; found iron and cap (DeYoung) West, 32.95'.				
1998; Survey (not recorded) by R.J. Kral; found 1/2" iron rod, same as 1989 & 1988 survey above.				
B. Description of corner evidence found M-6: 1/4 Cor. Common to Sec. 13. Found 1/2" Iron rod with partial cap at or standard County monument.	T27N-R7W. Kalkaska Tw	p: A-6: Sec. 18,T27N-R6		Added
No G.L.O. witnesses were found.				
C. Description of monument for corner	and accessories established	i to perpetuate locating the p	osition of the corner:	
M-6: 1/4 Car. Common to Sec. 13.	T27N-R7W. Kalkaska Tw	p: A-6: Sec. 18.T27N-R6	W. Excelsior Twp.	
Found 1/2" iron rod with partial cap at c	orner; 10" East of centerline	N-S road (Rosenburg Road): Rautied by P	found iron cap (N. DaYoung) West 32.95'.	Added
N 23°E, 25.32', 3," Elm, set nail and teg	ı	D 1 2/5 .10	IOO Kalkaeka Comby	
N 52°W, 13.03, 5" Elm, set neil and tag S 27°E, 21.60', 5" Elm, set neil and tag		Chairman C	egne source	
West 32.95', iron and cap (N. DeYoung)			7-14-01	
Kalkaska County Paer Grown accented th	ne shave manument as a car	Date	ent of the position of the original corner.	
namaka bounty i asi aroap abooptod ti	-)	STOP CHARLOTTER TO STOP TO STO	The project of the original comment	
Signed by /- Lander	Jamo:	n	ata Z-15-01	
Signed by Cally Surveyor's Michigan License No. 2459)4			
	Kalkaska County Jos	P. P. R.	7/18/2001 10:280 MEV	18, Jan. 28, 187 D May 14,1971 1680 Jan., 1883 1680 Oct., 1995