LAND CORNER RECORDATION CERTIFICATE

For corners in	Filing Require	ment of Act 74, Mich. P.A. 19	970
KALKASKA (County)	Located In:	Corner Code #	SURVEY & REMONUMENTATION
2000 REMONUMENTATION 1. Public Land Survey	T <u>27N</u> R <u>8W</u> TR T R	A-10	FEB 26 2001
Property Controlling in Section Miscellaneous Property in Sec.	TR S TR S TR S TR		SECTION
4. Lot No, Reco	orded Plat		
5. Private Claims			1 A B C D E F G H I J K L M 2 - 6 - 5 - 4 - 3 - 2 - 1
that under requirements of P.A. and 2 above were in conforms manual of survey instructions Management or by a decree of and 5 above were in conforma	a field survey on <u>NOVEMBER</u> . 74, Michigan P.A. of 1970, the cance with regulations and rules the of the United States Department a Court of Law and for that the conce with the rules of the Michigan billshed, re-established, monumente	corner points mentioned in lines 1 stretches as required in the current to 1 to	3 4 - 7 - 8 - 9 - 10 - 11 - 12 - 5 6 - 18 - 17 - 16 - 15 - 14 - 13 - 7 8 - 19 - 20 - 21 - 22 - 23 - 24 - 9 9
NOTE: Not more than 2 come on this certificate.	rs, all in the same town and range,	may be recorded	1 30 29 28 27 26 25 11 12 31 32 33 36 35 36
A. Description of original monument and accessories and/or subsequent restoration: A-10: 1/4 corner common to Section 30, T27N-R8W and Section 25 T27N-R9W: Oak post witnessed by a Yellow Pine 12" S47°W 8 links and Yellow Pine 14" N61°E 47 links, U.S. resurvey by Lucius Lyon dated 1850. A survey by W. S. Merrill, (Co. Surveyor), dated May 11, 1904 gives no corner type or witnesses. Original corner, M. Schaef, (State Surveyor) index for T27N-R9W, dated around 1930 and on file in the field office of the DNR in Traverse City. Set 1" iron bar on straight line and single proportion between two recovered corners, Land Corner Record by J. L. Wilcox, dated 1-15-73 and recorded in Liber 1 Page 175 of the Land Corner Records of Kalkaska County.			
A-10: 1/4 corner common to Found 1" iron bar as recorded in the U.S. bearing tree to the Nor perpetuation of the position of the cap stamped GRAND TRAVERS	theast, and established a corner ba- he orignal corner. Monumented thi E COUNTY REMONUMENTATION, I of Kalkaska County Land Corner F	ection 25 T27N-R9W: County Land Corner Records. Also sed on this probable U.S.R.T. position with a 2 1/2" x 30" flang 15" below the surface of roads Nor	o found what appeared to be the probable remains of on and is accepted as a careful and faithful ged bottom gelvanized iron pipe with 3 1/4" brass rth, South, East, and West. This corner position is Liber 1 Page 175 of the Kalkaska County Land
LCRC by Robert F. Mitchell 12-28-1993 recorded in Liber 3 page 471 Grand Traverse County Records; N 48° W, 8" White Pine, 38.82'; S 32°E, 10" Red Pine, 72.83'; S 29° W, 6" Red Maple, 60.76'; N 33°W, 13" Red Pine, 67.56'; S 04°59'E, 1" iron rod, 25.28'.			
Comer approved by the Grand T	raverse County Peer Raview Group	on 12-15-93.	AND OF MICHAEL
C. Description of monument for corner and accessories established to perpetuate locating the position of the corner: A-10: 1/4 corner common to Section 30. T27N-R8W and Section 25 T27N-R9W; Found Grand Traverse County Standard Monument 15" below the surface of roads North, South, East, and West. N48*W - 8" White Pine - 32.82' S32°E - 10" Red Pine - 72.83' S29°W - 6" Maple - 60.76' N33°W - 13" Red Pine - 67.56' S04°59'E - 1" Iron rod - 25.28' Kalkaska County Peer Group accepted the above monument as a careful and faithful gerpetuation of the position of the original corner.			
Ratified by Peer Gr P.A. 345 - 1990 Ka Chairman Date	oup kaska County 42 Fills (1)		

3026912 Page: 1 of 1 02/16/2001 10:28A County Joan Hall, Register LB: 8 PG: 241

Signed by Surveyor's Michigan License No. 24594

2-15-0

DFESSIONAL SURVEYORS, JAN. 28, 1971 PEVISED MAY 14,1976 REVISED JAN., 1983 NEVISED OCT., 1986