

FEB 14 1997

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970
KENT COUNTY REMONUMENTATION

For corners in

| | | |
|------------------------------------|---|-----------------------|
| <u>Kent</u> (County) | Located in: Caledonia Township | Corner Code # |
| 1. Public Land Survey | T <u> </u> R <u> </u> | |
| | T <u> </u> R <u> </u> | |
| | T <u> </u> R <u> </u> | |
| | T <u> </u> R <u> </u> | |
| 2. Property Controlling in Section | S <u>24</u> T <u>5N</u> R <u>10W</u> | West Witness Monument |
| 3. Miscellaneous Property in Sec. | S <u> </u> T <u> </u> R <u> </u> | 364.95' West of M-7 |
| | S <u> </u> T <u> </u> R <u> </u> | |

other code #12

STATE OF MICHIGAN
COUNTY OF KENT
RECEIVED FOR RECORD
96 NOV -8 AM 9:25
REG. OF DEEDS
Lucy Bond

9580

Register of Deeds Stamp & File Number

4. Lot No. , Recorded Plat
5. Private Claims

I, Randy Kolehouse, in a field survey on May 3 19 96, do hereby certify that under requirements of P.A. 74 Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

| | | | |
|-----------|----------------|-----------------|--------------------------------------|
| M-7C 1817 | G.L.O. Notes | L. Lyon | Corner in Lake - Set Temporary Point |
| 1992 | L.C.R.C. #6552 | T. Chettleburgh | Set K.C. Monument with Witness Cap |
| 1995 | L.C.R.C. #8158 | K. Breitels | K.C. Monument |

P.A. 345 1990 KENT COUNTY
PEER APPROVED 8/22/96
CHAIRMAN *Harry Huber*

Note: This corner is not common with A-7, T5N, R9W.

This corner was originally approved by the Kent County Remonumentation Peer Group and monumented by T. Chettleburgh on 5/29/92 and was recorded per L.C.R.C. #6552.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

M-7C Found a Standard Kent County Monument at the C/L of Dygert Drive 50' ± South of the C/L of 84th Street (bit.) running East and West as set by T. Chettleburgh at the intersection of the South line of Section 13 (North line Section 24) and C/L of Dygert Drive per L.C.R.C.'s #6552 and #8158. Corner is 364.95' West of M-7, T5N, R10W.

L.C.R.C. #6552

L.C.R.C. #8158

KC Remon tag NW side Power Pole N 53° E 45.78'
KC Remon tag NW side 27" Hickory N 79° E 67.05'
Con. Plat Monument S 40° E 45.81'
KC Remon tag SE side Power Pole S 33° W 39.05'
KC Remon tag SW side Tri-8" Maple N 53° W 87.57'

Nail & KC Remon. tag NW side Power Pole N 53° E 45.80'
Nail & KC Remon. tag NW side 27" Hickory N 79° E 67.05'
Nail & KC Remon. tag SE side Power Pole S 33° W 39.10'
Nail & KC Remon. tag SW side Tri. 8" Maple N 53° W 87.63'
Plat Monument S 40° E 45.86'

The selected location is accepted by me and is generally accepted by professional surveyors as the best available evidence of the position of the original corner.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

M-7C Standard Kent County Monument

Nail & K.C. remon. tag on NW side Power pole N 53° E 45.80'
Nail & K.C. remon. tag on NW side 27" Hickory N 79° E 67.05'
Nail & K.C. remon. tag on SE side Power pole S 33° W 39.10'
Nail & K.C. remon. tag on SW side Tri. 8" Maple N 53° W 87.63'
Plat Mon. S 40° E 45.86'
K.C. Mon. @ L-7, T5N, R10W, West 2280.15'

Signed by *Randy J. Kolehouse*

Date 10/8/96

EARTH TECH

Surveyor's Michigan License No. 25854

