

SEP 13 1995
\$7.00
\$2.00 COMMISSION

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970
KENT COUNTY REMONUMENTATION

For corners in

Kent
(County)

Located in:

Corner Code #

- | | | | |
|------------------------------------|------|-------|------|
| 1. Public Land Survey | T 5N | R 12W | E-10 |
| | T | R | |
| | T | R | |
| | T | R | |
| 2. Property Controlling in Section | S | T | R |
| | S | T | R |
| 3. Miscellaneous Property in Sec. | S | T | R |
| | S | T | R |

4. Lot No. _____, Recorded Plat _____
5. Private Claims _____

REG. OF DEEDS

8593

95 AUG 28 AM 10:50

STATE OF MICHIGAN
COUNTY OF KENT
RECEIVED FOR RECORD

Register of Deeds Stamp & File Number

I, Randy Kolehouse, in a field survey on April 11 19 95, do hereby certify that under requirements of P.A. 74 Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

E-10	1831	G.L.O. Notes	Mullett	Set Post
	1945	Wit. Map	K.C. Surveyor	Leaded Stone
	1972	L.C.R.C. #212	Exxel Engineering	Found Stone
	1982	L.C.R.C. #2815	Jonker	Found "T" Iron over Stone/Set K.C. Monument
	1988	L.C.R.C. #4620	Olson, Meyers & May	K.C. Monument

P.A. 345 1980 KENT COUNTY

PEER APPROVED 8/29/95
CHAIRMAN Tammy Huber

This corner was originally approved by the Kent County Remonumentation Peer Group and monumented by Jonker Land Surveys on 3/26/82 and was recorded per L.C.R.C. #2815.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

E-10 Found standard Kent County Monument at the C/L of Ivanrest Avenue per L.C.R.C.'s #2815 and #4620 as set by Jonker Land Surveys in place of a "T" iron over a leaded stone which checked L.C.R.C.'s #212, #2815 and #4620 and Kent County Surveyor Wit. Map (1945).

L.C.R.C. #2815

L.C.R.C. #4620

Remon. tag on E side 22" W Cherry S25°W 74.83'
Remon. tag on N side 12" Maple S83°W 44.89'
Remon. tag on S side p. pole N63°W 75.60'

Remon tag on E side 24" W. Cherry S 25 W 74.72'
Remon tag on N side 14" Maple S 83 W 44.90'
Remon tag & nail on S side P pole N 63 W 75.60'
Nail & tag in NE side 10" Maple N 35 E 42.97'
Leaded stone W 32.68'
On C/L N-S pvt., in line N edge woods to W

The selected location is accepted by me and is generally accepted by professional surveyors as the best available evidence of the position of the original corner.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

E-10 Standard Kent County Monument

Stone w/lead plug N 90° W 32.68'
Nail & K.C. remon. tag on E side 24" W Cherry S 25° W 74.72'
Nail & K.C. remon. tag on N side 14" Maple S 83° W 44.90'
Nail & K.C. remon. tag on S side P. pole N 63° W 75.60'
Nail & K.C. remon. tag on NW side 10" Maple N 35° E 42.97'

Signed by Randy J. Kolehouse Date 8/21/95

EARTH TECH

Surveyor's Michigan License No. 25854