

SEP 1 5 1995

COMMISSION

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970
KENT COUNTY REMONUMENTATION

For corners in

Kent (County)	Located in:	Corner Code #
1. Public Land Survey	T <u>5N</u> R <u>12W</u>	<u>H-7</u>
	T _____ R _____	_____
	T _____ R _____	_____
	T _____ R _____	_____
2. Property Controlling in Section	S _____ T _____ R _____	_____
	S _____ T _____ R _____	_____
3. Miscellaneous Property in Sec.	S _____ T _____ R _____	_____
	S _____ T _____ R _____	_____

STATE OF MICHIGAN
COUNTY OF KENT
RECEIVED FOR RECORD
95 AUG 28 AM 10:52
REC. OF DEEDS
8620

Register of Deeds Stamp & File Number

4. Lot No. _____, Recorded Plat _____
5. Private Claims _____

I, Randy Kolehouse, in a field survey on April 7 19 95,
do hereby certify that under requirements of P.A. 74 Michigan P.A. of 1970, the corner points
mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required
in the current manual of survey instructions of the United States Department of the Interior, Bureau of
Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3,
4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a
Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered,
found as expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded
on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

H-7	1831	G.L.O. Notes	Mullett	Set Post
	1950	Wit. Map	K.C. Surveyor	Leaded Stone
	1974	L.C.R.C. #765	Exxel Engineering	Found 1/2" Iron in Mon. Box
	1981	L.C.R.C. #2303	Nederveld & Jonker	Found 1/2" Iron in Mon. Box/Set K.C. Monument
	1991	L.C.R.C. #6322	Chris Marschall	K.C. Monument

P.A. 345 1990 KENT COUNTY

PEER APPROVED 5/25/95

CHAIRMAN Randy Kolehouse

This corner was originally approved by the Kent County Remonumentation Peer Group and monumented by Nederveld &
Jonkeron 9/3/81 and was recorded per L.C.R.C. #2303.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

H-7 Found standard Kent County Monument in a monument box on the C/L of 84th Street running E-W per L.C.R.C.'s shown
above as set by Nederveld & Jonker in place of a 1/2" iron in monument box they found which checked L.C.R.C. #765.

L.C.R.C. #2303

Nail & K.C. Remon. tag E side 8" Elm S10°E 86.70'
Nail & K.C. Remon. tag W side fence post N0°E 50.57'

L.C.R.C. #6322

Nail & Tag E sd 12" Maple N 5° W 72.73'
Nail & Tag W sd Fnd. Post N 00° E 50.54'
Nail & Tag SW sd U.P. S 66° E 123.25'
Nail & Tag SW sd 14" Pine S 35° E 44.11'
Nail & Tag W sd 18" Elm S 14° E 86.76'

The selected location is accepted by me and is generally accepted by professional surveyors as the best available evidence
of the position of the original corner.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

H-7 Standard Kent County Monument in a Monument Box

Nail & K.C. remon. tag on E sd 12" Maple N 5° W 72.73'
Nail & K.C. remon. tag on W sd Fnd. Post N 00° E 50.54'
Nail & K.C. remon. tag on SW sd Utl. pole S 66° E 123.25'
Nail & K.C. remon. tag on SW sd 14" Pine S 35° E 44.11'
Nail & K.C. remon. tag on W sd 18" Elm S 14° E 86.76'

Signed by

Randy J Kolehouse
EARTH TECH

Date

8/21/95

Surveyor's Michigan License No.

25854

