

JAN 23 1996

COMMISSION

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970
KENT COUNTY REMONUMENTATION

For corners in

Kent (County)	Located in:	Corner Code #
1. Public Land Survey	T <u>5N</u> R <u>12W</u>	<u>J-12</u>
	T _____ R _____	_____
	T _____ R _____	_____
	T _____ R _____	_____
2. Property Controlling in Section	S _____ T _____ R _____	_____
	S _____ T _____ R _____	_____
3. Miscellaneous Property in Sec.	S _____ T _____ R _____	_____
	S _____ T _____ R _____	_____

4. Lot No. _____, Recorded Plat _____
5. Private Claims _____

I, Randy Kolehouse, in a field survey on April 6 19 95, do hereby certify that under requirements of P.A. 74 Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

J-12 This corner was not originally set by the G.L.O.

1945-1966	Wit. Map	K.C. Surveyor	1" Iron
1980	L.C.R.C. #1344	Exxel Engineering	Set Capped Re-rod at Int. of 1/4 Lines
1991	L.C.R.C. #6182	Chris Marshall	Found Capped Re-rod at Int. of 1/4 Lines/Set K.C. Mon.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

J-12 Found Standard Kent County Monument as set by Chris Marshall in place of a capped record set by Exxel Engineering at the intersection of 1/4 lines per L.C.R.C.'s #1344 and #6182. Monument is 1.5' North of the south edge of 104th Street and 0.1' North of the intersection of 1/4 lines. Accepted Kent County Monument as Center Section.

L.C.R.C. #6182

Nail and remon tag in SW Root 40" Maple (1' above ground) N65°E 148.00'
Nail and remon tag in SW Root 22" Maple N47°E 170.46'
Nail and remon tag in W side 8" Elm S15°W 22.91'
Center of 3" Ash N75°E 186.54'

P.A. 345 1990 KENT COUNTY

PEER APPROVED 8/24/95

CHAIRMAN Harry Huber

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

■-12 Standard Kent County Monument

Nail & K.C. remon. tag in SW root 40" Maple N 65° E 148.00'
Nail & K.C. remon. tag in SW root 22" Maple N 47° E 170.46'
Nail & K.C. remon. tag in W root 8" Elm S 15° W 22.91'
Nail & K.C. remon. tag in center root 3" Ash N 75° E 186.54'
Nail & K.C. remon. tag in top of wood post South 19.68'
SE cor. block porch N 60° E 197.75'

igned by Randy J. Kolehouse Date 12/22/95

EARTH TECH

urveyor's Michigan License No. 25854

REG. OF DEEDS

8897

Register of Deeds Stamp & File Number

95 DEC 28 PM 2:20

STATE OF MICHIGAN
COUNTY OF KENT
RECEIVED FOR RECORD

	A	B	C	D	E	F	G	H	I	J	K	L	M
2	6	5	4	3	2	1							
3													
4	7	8	9	10	11	12							
5													
6	18	17	16	15	14	13							
7													
8	19	20	21	22	23	24							
9													
10	30	29	28	27	26	25							
11													
12	31	32	33	34	35	36							
13													

