

\$7.00  
\$2.00

JAN 23 1996

COMMISSION LAND CORNER RECORDATION CERTIFICATE  
Filing Requirement of Act 74, Mich. P.A. 1970  
KENT COUNTY REMONUMENTATION

For corners in

Kent  
(County)

Located in:

Corner Code #

- |                         |             |              |             |
|-------------------------|-------------|--------------|-------------|
| 1. Public Land Survey   | T <u>5N</u> | R <u>12W</u> | <u>L-12</u> |
|                         | T           | R            |             |
|                         | T           | R            |             |
|                         | T           | R            |             |
| 2. Property Controlling | S           | T            |             |
| in Section              | S           | T            |             |
| 3. Miscellaneous        | S           | T            |             |
| Property in Sec.        | S           | T            |             |

REG. OF DEEDS

8898

95 DEC 28 PM 2:20

STATE OF MICHIGAN  
COUNTY OF KENT  
RECEIVED FOR RECORD

Register of Deeds Stamp & File Number

4. Lot No. \_\_\_\_\_, Recorded Plat \_\_\_\_\_  
5. Private Claims \_\_\_\_\_

I, Randy Kolehouse, in a field survey on April 6 19 95, do hereby certify that under requirements of P.A. 74 Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

L-12 This corner was not originally set by the G.L.O.

?? West County Wit. Map Iron  
1981 L.C.R.C. #1836 Exxel Engineering Set Capped Re-rod at Int. of 1/4 Lines

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

L-12 Found capped iron set by Exxel Engineering at the intersection of 1/4 lines per L.C.R.C. #1836. Capped re-rod is at the intersection of 1/4 lines. Accepted capped re-rod as Center Section.

L.C.R.C. #1836

Nail in SE sde 14" W. Cherry S 22° W 5.54'  
Nail in N sde 26" W. Cherry S 58° W 3.41'  
Nail in NE sde 12" Ash N 54° W 25.39'

P.A. 345 1990 KENT COUNTY

PEER APPROVED 8/24/95

CHAIRMAN Randy Kolehouse

The selected location is accepted by me and is generally accepted by professional surveyors as the best available evidence of the position of the original corner.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

L-12 Set Standard Kent County Monument in Place of Capped Re-rod

Nail & K.C. remon. tag in E root 16" W. Cherry S 20° W 5.94'  
Nail & K.C. remon. tag in E face 36" Beech S 40° E 18.08'  
Nail & K.C. remon. tag in N face 36" W. Cherry S 58° E 3.84'  
Nail & K.C. remon. tag in W face 8" Ash N 54° W 26.05'

Signed by Randy J. Kolehouse  
EARTH TECH

Date

12/22/95

Surveyor's Michigan License No. 25854

