

\$2.00  
\$2.00

SEP 13 1995

RECORDED

LAND CORNER RECORDATION CERTIFICATE  
Filing Requirement of Act 74, Mich. P.A. 1970  
KENT COUNTY REMONUMENTATION

For corners in

Kent  
(County)

Located in:

Corner Code #

1. Public Land Survey

T 5N R 12W

M-7

T \_\_\_\_\_ R \_\_\_\_\_

T \_\_\_\_\_ R \_\_\_\_\_

T \_\_\_\_\_ R \_\_\_\_\_

2. Property Controlling  
in Section

S \_\_\_\_\_ T \_\_\_\_\_ R \_\_\_\_\_

S \_\_\_\_\_ T \_\_\_\_\_ R \_\_\_\_\_

3. Miscellaneous  
Property in Sec.

S \_\_\_\_\_ T \_\_\_\_\_ R \_\_\_\_\_

S \_\_\_\_\_ T \_\_\_\_\_ R \_\_\_\_\_

4. Lot No. \_\_\_\_\_, Recorded Plat \_\_\_\_\_

5. Private Claims \_\_\_\_\_

REG. OF DEEDS

95 AUG 28 AM 10:55

STATE OF MICHIGAN  
COUNTY OF KENT  
RECEIVED FOR RECORD

8670

Register of Deeds Stamp & File Number

I, Randy Kolehouse, in a field survey on March 15 19 95, do hereby certify that under requirements of P.A. 74 Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

M-7	1817	G.L.O. Notes	L. Lyon	Set Post	P.A. 345 1990 KENT COUNTY
	1936	Wit. Map	K.C. Surveyor	Iron	PEER APPROVED <u>6/27/95</u>
	1963	Wit. Map	K.C. Surveyor	1/2" Iron	CHAIRMAN <u>Hampshire</u>
	1975	L.C.R.C. #815	Exxel Engineering	Found 1/4" Iron	
	1980	L.C.R.C. #1530	Exxel Engineering	Found 1/4" Iron/Set K.C. Monument	
	1991	L.C.R.C. #6367	Chris Marschall	K.C. Monument	

This corner was originally approved by the Kent County Remonumentation Peer Group and monumented by Exxel Engineering on 12/10/80 and was recorded per L.C.R.C. #1530.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

M-7 Found standard Kent County Monument at the C/L intersection of Division Avenue running N-S and 84th Street running E-W per L.C.R.C.'s shown above as set by Exxel Engineering in place of a 1/4" iron they found which checked L.C.R.C. #815 and K.C. Surveyor's Wit. Map. This point is on the Town line and is 15.54' South of the SW cor., Sec. 18, T5N R11W.

L.C.R.C. #1530

L.C.R.C. #6367

"X" in top of concrete R.O.W. marker N23°E 139.92'  
"X" in top concrete R.O.W. marker S50°E 56.87'

"X" in top of conc R.O.W. Marker N 23 E 140.00'  
"X" in top of conc R.O.W. Marker S 50 E 56.87'  
Nail & Tag SE sd Guy Pole N 45 E 75.29'  
Nail & Tag W sd U.P. N 45 W 60.05'  
Nail & Tag SE sd U.P. S 45 W 59.83'

The selected location is accepted by me and is generally accepted by professional surveyors as the best available evidence of the position of the original corner.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

M-7 Standard Kent County Monument

Nail & K.C. remon. tag on SW side P. pole N 40° W 60.06'  
"X" in top R.O.W. marker N 20° E 140.02'  
Nail & K.C. remon. tag on SE side Guy pole N 45° E 75.31'  
"X" in top R.O.W. marker S 50° E 56.86'  
Nail & K.C. remon. tag on P. pole S 45° W 59.84'

Signed by Randy J. Kolehouse  
EARTH TECH

Date 8/21/95

Surveyor's Michigan License No. 25854

