

JAN 23 1996

COMMISSION

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970
KENT COUNTY REMONUMENTATION

For corners in

Kent
(County)

Located in:

Corner Code #

- | | | | | | |
|------------------------------------|---|----|---|-----|-----|
| 1. Public Land Survey | T | 5N | R | 12W | J-8 |
| | T | | R | | |
| | T | | R | | |
| | T | | R | | |
| 2. Property Controlling in Section | S | | T | | R |
| | S | | T | | R |
| 3. Miscellaneous Property in Sec. | S | | T | | R |
| | S | | T | | R |

4. Lot No. _____, Recorded Plat _____
5. Private Claims _____

I, Randy Kolehouse, in a field survey on April 21 19 95, do hereby certify that under requirements of P.A. 74 Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

J-8 This corner was not originally set by the G.L.O.

No record of corner in Kent County Surveyor's records

1991 L.C.R.C. #6181 Chris Marschall Set Set K.C. Monument by Intersection of 1/4 Lines

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

J-8 Found Kent County Monument as set by Chris Marschall per L.C.R.C. #6181 11.0' South of E-W fence. Monument is 0.35' North and 0.2' East of the intersection of 1/4 lines. Accepted Kent County Monument as Center Section.

L.C.R.C. #6181

Nail and Tag in W side 8" Oak N35°E 14.84'
Nail and Tag in SE side 10" Cherry N59°E 48.50'
Nail and Tag in N side 24" Cherry S87°E 46.24'
Nail and Tag in W side 24" Beech S36°E 74.81'
Nail and Tag in E side 30" Maple S29dW 12.98'

P.A. 345 1990 KENT COUNTY

PEER APPROVED 12/24/95

CHAIRMAN Randy J. Kolehouse

2. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

-8 Standard Kent County Monument

Nail & K.C. remon. tag in W side 8" Oak N35° E 14.84'
Nail & K.C. remon. tag in SE side 10" Cherry N 59° E 48.50'
Nail & K.C. remon. tag in N side 24" Cherry S 87° E 46.24'
Nail & K.C. remon. tag in W side 24" Beech S 36° E 74.81'
Nail & K.C. remon. tag in E side 30" Maple S 29° W 12.98'

Signed by Randy J. Kolehouse Date 12/22/95

EARTH TECH

Surveyor's Michigan License No. 25854

