REMONUMENTATION

MAR 08 1999

LAND CORNER RECORDATION CERTIFICATE Filing Requirement of Act 74, Mich. P.A. 1970

OLINEY DEMONBRACION

FOI CO	mers in SECTION	MENT COOKET REMONOMENTATION	A 4 C 225
<u></u>	Kent (County)	Located in: Vergennes Corner Code # Township	EC 14
1. P	ublic Land Survey	T 7N R 9W K-10W T R Witness Monument	MM 8: CONTRACTOR
	roperty Controlling	STRO	ther wde # 7
	liscellaneous roperty in Sec.	STR	Register of Deeds Stamp & File Number
		ecorded Plat	— ABCDEFGHIJKL
do he mention in the Land I 4 and Decre	ereby certify that under reported in lines 1 and 2 above current manual of survey Management or by a decrease 5 above were in conformer of a Court of Law; eas expressed below:	requirements of P.A. 74 Michigan P.A. of 1970, the corner point e were in conformance with regulations and rules therefore as require instructions of the United States Department of the interior, Bureau ce of a Court of Law and/or that the corner points mentioned in lines cance with the rules of the Michigan Board of Land Surveyors or by stablished, re-established, monumented, re-monumented, recovered erners, all in the same town and range, may be recorded	ts 5
A.	Description of original	monument and accessories and/or subsequent restoration:	12 31 32 33 34 35 3
K-10	1838 G.L.O. Not 1989 L.C.R.C. #1 1995 L.C.R.C. #1	5230 John Bueche Set K.C. Witness Mon. o 8262 William Byl K.C. Witness Monumen ally approved by the Kent County Remonumentation Peer Group	P.A. 345 1990 KENT COUNTY PEER APPROYED 2/19/98
D.	10/2/89 and was record	led per L.C.R.C. #5230. evidence found and/or method applied in restoring or reestabli	
В.	•		
K-10	Found a Standard Kent County Witness Monument 50.0' ± North of the C/L of Burroughs Road (gravel) per L.C.R.C.'s		

L.C.R.C. #5230

Nail & Remon, tag N side 10" Oak N 85° W 8.41'

Nail & Remon. tag E side 10" Oak N 5° W 13.27'

Nail & Remon. tag NW side 10" Oak N 80° E 22.45"

Nail & Remon. tag N side 12" Oak S 55° E 28.94'

Nail & Remon. tag W side group 4-14" Oaks S 20° W 23.63'

L.C.R.C. #8262

Nail & KC Remon. tag N. side 10" Oak N85°W 8.41' (m. 8.45')

Nail & KC Remon. tag E. side 10" Oak N05°W 13.27"

Nail & KC Remon. tag NW side 10" Oak N80°E 22.45' (m. 22.48')

Nail & KC Remon. tag N. side #12" Oak S55°E 28.94' (m. 28.89')

Nail & KC Remon. tag W. side group 14" Oaks S20°W 23.51' (m. 23.60')

The selected location is accepted by me and is generally accepted by professional surveyors as the best available evidence of the position of the original corner.

Description of monument for corner and accessories established to perpetuate locating the position of the corner: C.

K-10 Standard Kent County Witness Monument

Nail & K.C. remon, tag on N side 10" Oak N 85° W 8.45'

Nail & K.C. remon. tag on E side 10" Oak N 05° W 13.27"

Nail & K.C. remon, tag on NW side 10" Oak N 80° E 22.48'

Nail & K.C. remon, tag on N side 12" Oak S 55° E 28.89'

Nail & K.C. remon, tag on W side group 14" Oaks S 20° W 23.60'

C/L of gravel road, South 50.0' ±

Surveyor's Michigan License No.

Signed by

<u>25854</u>

OF MICH RANDY J. KOLEHOUSE

28 ST