

# SURVEY & REMONUMENTATION

MAR 03 1998

\$7.00  
\$2.00

## SECTION

## LAND CORNER RECORDATION CERTIFICATE Filing Requirement of Act 74, Mich. P.A. 1970 KENT COUNTY REMONUMENTATION

For corners in

Kent (County)	Located in:	Ada Township	Corner Code #
1. Public Land Survey	T _____	R _____	C-7
	T _____	R _____	
	T _____	R _____	
	T _____	R _____	
2. Property Controlling in Section	S _____	T 7N	R 10W
	S _____	T _____	R _____
3. Miscellaneous Property in Sec.	S _____	T _____	R _____
	S _____	T _____	R _____

4. Lot No. \_\_\_\_\_, Recorded Plat \_\_\_\_\_  
5. Private Claims \_\_\_\_\_

I, Randy Kolehouse, in a field survey on November 14 19 97, do hereby certify that under requirements of P.A. 74 Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

**NOTE:** Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

### A. Description of original monument and accessories and/or subsequent restoration:

C-7 1831 G.L.O. Notes Mullett Set Post  
1988 L.C.R.C. #4941 Exxel Engineering Set Witness Corners

P.A. 345 1990 KENT COUNTY

PEER APPROVED 11/26/97

CHAIRMAN Henry Huber

This corner was originally approved by the Kent County Remonumentation Peer Group and monumented by Exxel Engineering on 2/11/88 and was recorded per L.C.R.C. #4941.

### B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

C-7 Found a Standard Kent County Monument on the West bank of the Grand River 85' ± West of the waters edge and 15' ± North of a ditch running East and West per L.C.R.C. #4941 as set by Exxel Engineering.

L.C.R.C. #4941

Nail & tag SW sde Tw. 18" Oak N 35° W 41.48' (m. 41.26')  
Nail & tag N sde Tw. 12" W. Cherry N 90° W 7.78' (m. 7.80')  
Nail & tag N sde Tw. 20" Oak N 90° E 8.61' (m. 8.54')  
Nail & tag S sde Tw. 24" Oak N 60° E 50.67' (m. 50.34')  
Waters edge East 85' ±  
C/L E-W ditch South 15'

The selected location is accepted by me and is generally accepted by professional surveyors as the best available evidence of the position of the original corner.

### C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

C-7 Standard Kent County Monument

Nail & K.C. remon. tag on SW side Tw. 20" Oak N 35° W 41.26'  
Nail & K.C. remon. tag on N side Tw. 14" Wild Cherry N 40° W 7.80')  
Nail & K.C. remon. tag on N side Tw. 22" Oak N 90° E 8.54'  
Nail & K.C. remon. tag on S side Tw. 24" Oak N 60° E 50.34'

Signed by Randy J. Kolehouse Date 11/28/97  
EARTH TECH

Surveyor's Michigan License No. 25854

