KENT COUNTY REMONUMENTATION

STATE OF INCHIGAN COUNTY OF KENT RECEIVED FOR RECORD

LAND CORNER RECORDATION CERTIFICATE Filing Requirement of Act 74, Mich. P.A. 1970

93 MAR -9 11 1: 56

| T'A | r corners in | rining nequi | rement of Act 74, Mich. F | 'A. 1970 |
|------------|---|---|--|--|
| . (14) | s coners in | • | CANNON TWP | 1 08-11 |
| | Kent | Located In: | Corner Code ## | Children Color |
| 1 | Public Land Survey Cannon Township | T <u>8 - N_R 10 - M</u> T R T R | 170 | Prop Control |
| (1) | D | TR | | O-KAKK. |
| 7 | Property Controlling in Section | S R | | C 17 O A |
| 3. | Miscellaneous | S R | V 1 | 6734 |
| ·). | Property in Sec. | S T R S T R | | Register of Deeds Stamp & File Number |
| , | r roperty in Sec. | 5 I H | | 3-4-03 |
| 4. | Let No R | ecorded Plat | # No. 1 | 3 7 7 7 |
| 5 | | | | A B C D E F G H I J K L |
| | | | | 2 6 5 1 2 2 1 2 |
| | | | $S = I_{m+1}^{SB} \mathcal{A}_{m+1}$ | 4 7 8 9 9 10 11 12 12 |
| in l | hereby certify that under req ines 1 and 2 above were in | in a field survey on uirements of P.A. 74, Michigan P.A conformance with regulations and citions of the United States Depa | of 1970, the corner points ment nd rules, therefore as required i | ioned 6 18 17 16 15 14 13 |
| Mai | nagement or by a decree of a | Court of Law and/or that the corn the the rules of the Michigan Board | erpointsmentioned in lines 3, 4 | and 5 8 10 20 21 22 23 |
| Cot | art of Law; established, repressed below: | e-established, monumented, re- | monumented, recovered, four | nd as 9 29 28 27 26 25 |
| NO | OTE: Not more than 4 corners, all in the same town | | nd range, may be recorded | |
| | on this certificate. | | | 12 31 32 33 34 35 36 |
| Α. | Description of original n | nonument and accessories an | d/or subsequent restoration | |
| | M-12 | East 1/4 corner of Sect | ion 36 | at the state of th |

B Description of corner evidence found and/or method applied in restoring or reestablishing corner:

Corner is in Ratigan Lake

See PA - 132 Survey Recorded in Liber $\mathcal{R}^{\mathcal{S}}$, Page $\mathcal{A}^{\mathcal{O}}$ For Section Survey.

Set witness monument on East and West 1/4 line 1950 feet East of center of Section 36. and 706.09 feet West of the East 1/4 corner.



O Description of monument for corner and accessories established to perpetuate locating the position of the corner:

Set Standard Kent County Monument with wit. cap.

WITNESSES

| | q_{i} | · | | |
|---------------------------|---------------------|------------|-----|-------|
| Nail and Remon Tagin N. | side Twin 12" Maple | N - 65 - W | = | 13.07 |
| Nail and Remon Tag in N. | side Twin 14" Maple | N - 40 - W | | |
| -Natitand Hemon lagion Wi | side 12" Cherry | N - 05 - W | = . | 46.65 |
| Nail and Remon Tag in W | side 10" Maple | N - 40 - E | = . | 31.49 |
| Nail and Remon Tag in S | side 10" Willow | S - 80 - E | = | 12.16 |
| Nail and Remon Tag in . E | side 6" Willow | S - 35 - E | = | 17.00 |
| | | | | |

Iron on North line of W & W Plat - North - 36.2'

Signed by Thomas C. Live Date March 9, 1993

Surveyor's Michigan License No. 25874