

**SURVEY & REMONUMENTATION**

\$7.00  
\$2.00

MAR 08 1999

**KENT COUNTY REMONUMENTATION**

**LAND CORNER RECORDATION CERTIFICATE**  
Filing Requirement of Act 74, Mich. P.A. 1970

REG. OF DEEDS

*Lucy Sand*

38 NOV 16 AM 8:00

STATE OF MICHIGAN  
COUNTY OF KENT  
RECEIVED FOR RECORD

**SECTION**

For corners in

KENT COUNTY

(County)

Located In:

Corner Code #

1. Public Land Survey

T\_\_\_ R\_\_\_  
T\_\_\_ R\_\_\_  
T\_\_\_ R\_\_\_  
T\_\_\_ R\_\_\_

2. Property Controlling  
in Section

S 36 T 9N R 11W Wit Mon on  
S\_\_\_ T\_\_\_ R\_\_\_ N-S 1/4 line

3. Miscellaneous  
Property in Sec.

S\_\_\_ T\_\_\_ R\_\_\_  
S\_\_\_ T\_\_\_ R\_\_\_

other code  
# 2

10922

Register of Deeds Stamp & File Number

4. Lot No. \_\_\_\_\_, Recorded Plat \_\_\_\_\_  
5. Private Claims \_\_\_\_\_

I, Kirk Breitels, in a field survey on Nov. 2, 1998 do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and /or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

	A	B	C	D	E	F	G	H	I	J	K	L
1												
2	6		5		4		3		2		1	
3												
4	7		8		9		10		11		12	
5												
6	18		17		16		15		14		13	
7												
8	19		20		21		22		23		24	
9												
10	30		29		28		27		26		25	
11												
12	31		32		33		34		35		36	
13												

A. Description of original monument and accessories and/or subsequent restoration:

1837 GLO Whitcomb Not Set  
Survey Williams & Works Set PK Nail & tag on E-W 1/4 line per plats and C/L Prospect St.

P.A. 345 1990 KENT COUNTY

PEER APPROVED 10/22/98

CHAIRMAN *Fanny Huhner*

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

Found PK Nail with Williams & Works tag on E-W 1/4 line (per their plats of 1955) and the C/L Prospect St.  
Measured 1925.05' to West 1/4 corner and 785.19' to Central 1/4 corner as recorded in LCRC # 10921.

This PK Nail with Williams & Works tag is accepted by me and is generally accepted by professional surveyors as the best available evidence of the position of the Witness Corner.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

Set Kent County Witness Monument in place of the PK Nail with Williams & Works tag  
Nail & KC Remon. tag W. side MBT Pole S15°E 43.08'  
Nail & KC Remon. tag E. side P. Pole S25°W 59.91'  
NE corner porch foundation at grade S80°W 53.89'  
Nail & KC Remon. tag E. side P. Pole N15°W 55.84'  
Nail & KC Remon. tag E. side P. Pole N20°E 50.29'  
SW corner house #244 foundation N85°E 70.82'



Signed by *Kirk Breitels*  
Surveyor's Michigan License No. 30077

Date 11/12/98