SURVEY & C T	SHOULD BE
1993 Other	Carren A 1110 100
Kent County	· · · · · · · · · · · · · · · · · · ·
COMMISSION LAND CORNER REC	ORDATION C
For corners in	of Act 74, Min
Kent Located In: Co	rner CHEMONUMENTATION
(County)	To a Code
1. Public Land Survey	Ther Code MAY 0 9 1996
2. Property Controlling S 23 T 10N R —9W Spe	COMMISSION 790
in Section S T R	
3. Miscellaneous       S T R         Property in Sec.       S T R	Register of Deeds Stamp & File Number
4. Lot No, Recorded Plat	A B C D E F G H I J K L M
5. Private Claims	2 - 6 - 5 - 4 - 3 - 2 - 1
Taku C. Busaka	4 7 8 9 10 11 12
l, John C. Bueche, in a field survey on April do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, t	he corner points mentioned
in lines 1 and 2 above were in conformance with regulations and rules to current manual of survey instructions of the United States Department of	nerefore as required in the
Management or by a decree of a Court of Law and/or that the corner points r above were in conformance with the rules of the Michigan Board of Land Si	
Court of Law, established, re-established, monumented, re-monumer expressed below:	ted, recovered, found as
NOTE: Not more than 4 corners, all in the same town and range on this certificate.	12 31 32 33 34 35 36
Description of original monument and accessories and/or sub-	sequent restoration:
This point never set by G.L.O.	
	<del>-</del>
B. Description of corner evidence found and/or method applied in a contract of the corner evidence found and/or method applied in a contract of the corner evidence found and/or method applied in a corner evidence found and a corner evidence found and a corner evidence for a corne	
Set witness monument 746.87' N. of S 1/4 Co	or Sec 23 on the N-S 1/4 Line of Sec 23.
· · · · · · · · · · · · · · · · · · ·	
The state of the s	•
<del>.</del>	
C. Description of monument for corner and accessories establish	led to perpetuate locating the position of the corner:
Set Std. K.C. Mon. (Harrison 4" x 30 cor. Sec. 23 on the N-S 1/4 line of Nail & K.C. Remon. Tag in N side 6" Nail & K.C. Remon. Tag in NE side db Nail & K.C. Remon. Tag in NW side 10 Nail & K.C. Remon. Tag in S side 12" Top bank to Lake S 30'± Meas. by EDM	Sec. 23 Oak S 85° E 43.73' Ol. 10" W. Cherry S 35° E 24.88'
	SURVEYOR No.
Signed by John C Busche	Date
Surveyor's Michigan License No. 13027	FORM APPROVED BY MICHIGAN STATE ROARD OF LAND SURVEYDRE 184 1971
•	REVISED MAY 14, 1975 REVISED JAN., 1983