

SURVEY & REMONUMENTATION

MAR 19 1997

COMMISSION

LAND CORNER RECORDATION CERTIFICATE

Filing Requirement of Act 74, Mich. P.A. 1970

For corners in

Keweenaw

(County)

Located In:

Corner Code #

1. Public Land Survey

T 58 R 29

T 58 R 29

T R

T R

2. Property Controlling

S T R

in Section

S T R

3. Miscellaneous

S T R

Property in Sec.

S T R

4. Lot No. , Recorded Plat

5. Private Claims

I-2

I-3

REGISTER'S OFFICE

County of Keweenaw } SS

Received for Record, the

day of December A.D. 1996

at 1:00 o'clock P.M. and Recorded

in Liber 1 of L.C.R.

on page 150

Robert Rosenberger, Deputy
Register of Deeds

Register of Deeds Stamp & File Number

I, John I. Haataja, in a field survey on September 20, 19 96, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

I-2 East 1/4 corner Sec. 3

Wood Post

Pine 7" N 60 E 13 lks.

Spruce 9" S 50 W 42 lks.

I-3 S.E. corner Sec. 3

Wood Post

Sugar 16" S 40 E 60 lks.

Pine 14" N 34 W 15 lks.

Description of corner evidence found and/or method applied in restoring or reestablishing corner:

I-2 FND 1 1/2" pipe, corner checks to be N 15 E 67.08' of correct location by single proportionate measurement between N.E. & S.E. corners. Removed 1 1/2" pipe and set 1" pipe with brass cap at correct location.

I-3 FND 1 1/2" pipe in place. As FND in Liber 1 of L.C.R. Page 46.

Ratified by Peer Group
In accordance with P.A. 345
Co. Rep. James H. Haataja
Date 12/6/96

Description of monument for corner and accessories established to perpetuate locating the position of the corner:

I-2 East 1/4 corner Sec. 3

1" pipe with brass cap

10" Oak S 46 W 17.48'

12" Oak N 10 E 22.76'

5" Maple N 74 E 15.28'

4" W. Pine S 34 E 41.35'



I-3 S.E. corner Sec. 3

1 1/2" pipe with brass cap

10" Oak S 15 E 26.88'

10" Maple N 82 E 26.30'

4" Maple N 7 E 6.41'

10" Cedar S 69 W 29.08'

by John I. Haataja
or's Michigan License No. 19833

Date

11/27/96