

# SURVEY & REMONUMENTATION

AUG 06 1996

COMMISSION

## LAND CORNER RECORDATION CERTIFICATE Filing Requirement of Act 74, Mich. P.A. 1970

For corners in

Kalamazoo  
(County)  
Ross Twp.  
1. Public Land Survey  
2. Property Controlling in Section  
3. Miscellaneous Property in Sec.

Located In: T 15 R 9W  
S T R  
S T R  
S T R  
S T R

Corner Code # G-04

STATE OF MICHIGAN  
COUNTY OF KALAMAZOO  
RECEIVED FOR RECORD  
96 JUN 7 PM 2 27  
CLERK - REGISTER  
LIBER 2 PAGE 034  
Register of Deeds Stamp & File Number

4. Lot No. \_\_\_\_\_, Recorded Plat \_\_\_\_\_  
5. Private Claims \_\_\_\_\_

I, Robert E. Snell, in a field survey on Feb. 8, 1996 do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and /or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2		6		5		4		3		2		1	
3													
4		7		8		9		10		11		12	
5													
6		18		17		16		15		14		13	
7													
8		19		20		21		22		23		24	
9													
10		30		29		28		27		26		25	
11													
12		31		32		33		34		35		36	
13													

### A. Description of original monument and accessories and/or subsequent restoration:

1825: United States Government Surveyors; set 1/4 Section post.

Wh. Oak 18" S. 84° W. 27 lks.  
Wh. Oak 15" S. 02° W. 36 lks.

1883: Found stake, stone and stump of witness of resurvey correct. Bored 3 ft. put stone in bottom and 2 ft. earthen post over, with stone around. No trees near.

### B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

1982: Robert E. Snell, R.L.S. #9734; L.C.R.C. L-1, P-868 found tile with ring of stones around.

24" Wild Cherry N. 10° W. 22.63' -- in North and South fence line  
10" Maple West 20.0' -- 28" Wild Cherry South 32.02'

1996: Found tile from above witnesses.

RATIFIED  
BY KALAMAZOO COUNTY  
REMONUMENTATION  
PEER GROUP  
3-21-1996

### C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

G-04: East 1/4 post, Section 9, T. 1 S., R. 9 W., ratified by the Kalamazoo County Remonumentation Program Peer Group on March 21, 1996 and is accepted as a careful and faithful perpetuation of the position of the original corner. Found 3" round tile with "x" on top in a ring of stones as called for in 1883 remonumentation survey of F. Hodgman, County Surveyor. Placed remonumentation sleeve over tile.

PK Nail in East Side 28" W. Cherry  
PK Nail in Northeast Side 10" W. Cherry  
PK Nail in North Side 18" Maple  
PK Nail in Southwest Side 24" W. Cherry

South 32.36'  
S. 52° W. 15.96'  
S. 84° W. 19.60'  
N. 08° W. 22.50'

Signed by Robert E. Snell  
Surveyor's Michigan License No. 9734

Date 6-6-96