

SECTION

LIBER

2PAGE 444

For corners in **ALAMO TWP**
KALAMAZOO
(County)

Located In:

Corner Code #

		1S.	12W.	A-10
1. Public Land Survey	T	_____	R	_____
	T	_____	R	_____
	T	_____	R	_____
	T	_____	R	_____
2. Property Controlling in Section	S	_____	T	_____
	S	_____	T	_____
3. Miscellaneous Property in Section	S	_____	T	_____
	S	_____	T	_____

CLERK'S REGISTER

38 DEC 30 PM 12 00

STATE OF MICHIGAN
COUNTY OF KALAMAZOO
RECEIVED FOR RECORD

Register of Deeds Stamp & File Number

4. Lot No. _____, Recorded Plat _____
5. Private Claims _____

I, Allen H. McMachen, in a field survey on December, 1998, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Professional Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

[illegible]

A. Description of original monument and accessories and/or subsequent restoration:

Corner not placed by original government surveyors.

1875 - Ed Strong, Deputy Surveyor, "Found stake one U.S. remains"

1901 - W.H. Goss, D.C.S., (E $\frac{1}{4}$ corner, Section 25, Pine Grove Township) "Found stake & remains of one witness, set stake by old one. Alamo corner is 27.5 lks. (18.15') North.

1902 - Ed Strong, C.S., "Bisected West Section line of 30, set stake, iron & brick promised. Jog on County line at $\frac{1}{4}$ post is 28 lks. by this survey. Goss, County Surveyor for Van Buren County had just brushed and staked this Section line for Todd & we followed the line (map indicates measure from Northwest corner, Section 30 South 39.86 $\frac{1}{2}$ chains [2631.09'] to the West quarter corner, Section 30 and from West quarter corner, South 39.86 $\frac{1}{4}$ chains [2631.09'] to Southwest corner.

1915 - W.H. Goss, D.C.S., (E $\frac{1}{4}$ corner, Sec. 25, Pine Grove Twp.), Set 1 $\frac{1}{2}$ " pipe, 4' long, 4" Elm S. 33° 30' W. 25.5', 4" Elm N. 30° 30' W. 76', distance South is 39.83 chains (2628.78') to Southeast corner.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

No corner marker found. Reestablished position of corner by measuring North 28 lks. (18.48') as called for in 1902 from a standard Van Buren County Remonumentation Monument at the East quarter corner, Section 25, Pine Grove Township and placing a 30" Harrison Monument. Said monument was placed on line between said East quarter corner, Section 25, Pine Grove Township and the East quarter corner, Section 13, Pine Grove Township. Position of monument placed is 0.5' South of the Westerly extension of a line from a standard marker at the East quarter corner of Section 30, Alamo Township and a found iron at the Center quarter corner of Section 30, Alamo Township. Measured from monument placed at West quarter corner, Section 30 North 2630.36 feet to Northwest corner, Section 30.

RATIFIED
BY KALAMAZOO COUNTY
REMONUMENTATION
PEER GROUP
12-17-1998 *R*

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

This position not established by original government surveyors. 30" Harrison Monument placed per above description is accepted as the best available evidence of the position of the corner, Accessories:

Nail & Tab in S. side of U. Pole N. 75° W. 43.3'

Nail & Tab in 6" Maple S. 60° E. 73.75'

Chiseled "X" in top of concrete headwall S. 25° W. 24.64'

East quarter corner, Section 25, Pine Grove Township (Standard Van Buren County Remonumentation Monument) South 18.48'

14.5' North of centerline East-West road.

Signed by W. A. M. P. O'Brien Date 12/29/78

Surveyor's Michigan License No. 16935

FORM APPROVED BY MICHIGAN STATE BOARD OF PROFESSIONAL SURVEYORS, JAN. 28, 1971
REVISED MAY 14, 1975
REVISED JAN. 1983