

LAND CORNER RECORDATION CERTIFICATE  
Filing Requirement of Act 74, Mich. P.A. 1970

For corners in

Kalamazoo

(County)

Charleston Section 31

1. Public Land Survey

Located In:

Corner Code -#

T 2 S R 9 W

B-13

T R

T R

T R

T R

2. Property Controlling  
in Section

S T R

S T R

3. Miscellaneous  
Property in Sec.

S T R

S T R

4. Lot No. , Recorded Plat

5. Private Claims

I, Robert E. Snell, in a field survey on January 13, 19 94

do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

**NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.**

A. Description of original monument and accessories and/or subsequent restoration:

Original corner established by U.S. Government Survey in 1825-Set Post.

Y. Oak 16" North 15°-E 78 Lks (51.48')

Hickory 7" North 52°-W 60 Lks (39.60')

1983-F. Hodgeman County Surveyor-found stake of old survey and stump of hickory witness tree of resurvey, West 111 Lks (73.26'). Bored three feet, put one foot of stone in the bottom and two one-foot earthen post over with stone packed around.  
No witness near.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

Found solid clay tile with "X" marked on top with "T" iron fence post to North.

	A	B	C	D	E	F	G	H	I	J	K	L	M
2	6	5	4	3	2	1							
3													
4	7	8	9	10	11	12							
5													
6	18	17	16	15	14	13							
7													
8	19	20	21	22	23	24							
9													
10	30	29	28	27	26	25							
11													
12	31	32	33	34	35	36							
13													

**RATIFIED**  
**BY KALAMAZOO COUNTY**  
**REMONUMENTATION**  
**PEER GROUP**  
1-20-94

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

B-13 South 1/4 Post Section 31, T. 2 S., R. 9 W., ratified by Kalamazoo County Remonumentation Program Peer Group on January 20, 1994. Found solid clay tile with "X" as called for in F. Hodgeman remonumentation survey of 1883 and is accepted as a careful and faithful perpetuation of the position of the original corner. Placed remonumentation sleeve over tile and placed stones around.

Top of "T" Iron Fence Post

North 1.07'

Centerline of Farm Lane

West 21.0'

Bottom of Hill

East 20.0'

Vertical Pipe of Pivot

Irrigation over Concrete Pad North 813.5'

Tile is 2.7' below top of "T" Iron  
Fence Post in a rock pile.

Signed by

Date

Surveyor's Michigan License No.

9734