

LAND CORNER RECORDATION CERTIFICATE  
Filing Requirement of Act 74, Mich. P.A. 1970

94 APR 28 AM 9 11

For corners in

KALAMAZOO  
(County)

Located In:

Corner Code #

Sec. 17, Charleston Twp.

1. Public Land Survey

T 2 S R 9 W

C-5

2. Property Controlling  
in Section

S T R

3. Miscellaneous  
Property in Sec.

S T R

4. Lot No. , Recorded Plat

5. Private Claims

*James J. Jones*  
CLERK-REGISTER

LIBER 1 PG 1133

Register of Deeds Stamp & File Number

I, Robert E. Snell, in a field survey on February 21, 19 94,  
do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned  
in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the  
current manual of survey instructions of the United States Department of the Interior, Bureau of Land  
Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5  
above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a  
Court of Law; established, re-established, monumented, re-monumented, recovered, found as  
expressed below:

**NOTE: Not more than 4 corners, all in the same town and range, may be recorded  
on this certificate.**

A. Description of original monument and accessories and/or subsequent restoration:

1826-Original corner established by U.S. Government Survey-Set Post. Corner Sections 7, 8,  
17, and 18.

Wh. Oak 10" South 80° East 19 Lks  
Wh. Oak 7" North 42° West 35 Lks

1877-F.Hodgeman, County Surveyor-Found stone of former survey-correct by one U.S. Witness.  
1883-F.Hodgeman, County Surveyor-Replaced stone with 3' earthen post with stone around.

Wh. Oak 20" North 02° West 116 Lks

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

Found tile-3" round with "X" on top from 1939 Wilkins & Wheaton Witness.

24" Walnut North 14.85'  
24" Pine South 02° East 35.85'

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

C-5 Northwest Corner Section 17, T. 2 S., R. 9 W., ratified by Kalamazoo County Remonumenta-  
tion Program Peer Group on March 3, 1994. Found 3" round tile with "X" on top as called  
for in 1883 Remonumentation survey by F.Hodgeman and is accepted as a careful and faithf  
perpetuation of the original corner's position. Placed remonumentation sleeve over tile.

PK Nail in South Side 12" Walnut North 78° East 19.63'  
PK Nail in West Side Power pole South 16° West 47.82'  
PK Nail in North Side 30" Oak North 62° West 81.25'  
PK Nail in West side 18" Walnut North 06° East 5.05'

Signed by

*Robert E. Snell*  
9734

Date

4-26-94

Surveyor's Michigan License No.

	A	B	C	D	E	F	G	H	I	J	K	L	M
2	6		5		4		3		2		1		
3													
4	7		8		9		10		11		12		
5													
6	16		17		18		15		14		13		
7													
8	19		20		21		22		23		24		
9													
10	30		29		28		27		26		25		
11													
12	31		32		33		34		35		36		
13													

*R.E.S.*  
**RATIFIED  
BY KALAMAZOO COUNTY  
REMONUMENTATION  
PEER GROUP  
3-3-94**