

7
2

STATE OF MICHIGAN
COUNTY OF KALAMAZOO
RECEIVED FOR RECORD

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

94 APR 28 AM 9 11

For corners in

KALAMAZOO
(County)

Located In:

Corner Code #

James J. Jones
CLERK-REGISTER

LIBER 1 PG 1131

Register of Deeds Stamp & File Number

1. Sec. 8, Charleston
Public Land Survey

T 2 S R 9 W

D-5

2. Property Controlling
in Section

S T R

3. Miscellaneous
Property in Sec.

S T R

4. Lot No. , Recorded Plat

5. Private Claims

I, Robert E. Snell, in a field survey on February 7, 19 94,

do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

1826-Original corner established by U.S. Government Survey-Set & Post.

Wh. Oak 9" North 74° West 8 Lks
Wh. Oak 9" South 72° East 27 Lks

1883-F.Hodgeman, County Surveyor-Ran South 74° East, 9 Lks from stump of U.S. Bearing Tree and found rotted stake. Set 3' earthen post.

Wh. Oak 8" North 85° West 88 Lks
Hickory 10" South 02° East 276 Lks

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

Found 3" round tile with "Mushroom" top about 6" below surface from 1972 witness (LCRC)

20" W. Cherry South 01° East 26.57'
Railroad Tie South 11.15'
2" Oak North 40° West 7.15'

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

D-5 South & Post Section 8, T. 2 S., R. 9 W., ratified by Kalamazoo County Remonumentation Program Peer Group on March 3, 1994. Found 3" round tile with "Mushroom" top as called for in 1883 remonumentation survey by F.Hodgeman and is accepted as a careful and faithful perpetuation of the original corner's position. Removed "mushroom" head and placed remonumentation sleeve over tile.

PK Nail in West Side W. Branch of DbI 24" W. Cherry South 05° East 26.52'
PK Nail in East Side 5" Ash South 24° East 19.24'
PK Nail in West Side 6" Ash South 33° East 11.28'
PK Nail in West Side 11" Oak North 32° West 7.30'
Face of RR Tie Fence Corner West 0.30'
PK Nail in South Side 8" W.Cherry North 84° West 15.05'

Signed by

Robert E. Snell

Date

4-26-94

Surveyor's Michigan License No.

9734

R. J. Jones
**RATIFIED
BY KALAMAZOO COUNTY
REMONUMENTATION
PEER GROUP
3-3-94**