

SURVEY &
REMONUMENTATION

APR 27 1995

COMMISSION

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

STATE OF MICHIGAN
COUNTY OF KALAMAZOO
RECEIVED FOR RECORD

'94 DEC 6 PM 3 56

For corners in

Kalamazoo

(County)

Located In:

Corner Code ##

Charleston Township
1. Public Land Survey

T 2 S R 9 W

E-10

T R

T R

T R

S T R

S T R

S T R

2. Property Controlling
in Section

S T R

S T R

3. Miscellaneous
Property in Sec.

S T R

S T R

James J. Jans
CLERK-REGISTER

LIBER

1 PG 1185

Register of Deeds Stamp & File Number

4. Lot No. , Recorded Plat

5. Private Claims

I, Robert E. Snell, in a field survey on September 22, 19 94,
do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned
in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the
current manual of survey instructions of the United States Department of the Interior, Bureau of Land
Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5
above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a
Court of Law; established, re-established, monumented, re-monumented, recovered, found as
expressed below:

**NOTE: Not more than 4 corners, all in the same town and range, may be recorded
on this certificate.**

A. Description of original monument and accessories and/or subsequent restoration:
1826 - U.S. Government Survey-Set 1/4 Section Post

Elm 12" South 16° East 66 Lks
Wh. Oak 14" South 53° West 82 Lks

1883 - F. Hodgeman, County Surveyor-Found iron, brick of former survey and side stone 50 Lks
East. Bored down 2½' to a stone. Put brick over the stone and 1' earthen post on top
with stone around and noted.

Maple 8" South 21° East 149 Lks
Black Walnut 4" South 84½° East 123 Lks

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

1994 - Found tile in monument box, down 8".

Note: 1883 Black Walnut 4" South 84½° East 123 Lks=81.92' ("A") above
1994 Black Walnut 34" South 72° East 81.34' ("C") below

RATIFIED
BY KALAMAZOO COUNTY
REMONUMENTATION
PEER GROUP
11/17/94

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

E-10 West 1/4 Post Section 28, T. 2 S., R. 9 W., Ratified by the Kalamazoo County Remonumen-
tation Program Peer Group on November 17, 1994. Found 1' section of 3" round tile in
monument box and is accepted as a careful and faithful perpetuation of the original
corner's position. Placed remonumentation sleeve over tile.

PK Nail in West Side 58" Maple South 26° East 106.16' T CL 40th St
PK Nail in West Side 16" Locust South 32° East 66.12' West 3.4'
PK Nail in North Side 34" Walnut South 72° East 81.34'
"X" Chisled in North End Concrete Drive Culvert North 36° East 42.38'

Signed by

Surveyor's Michigan License No.

9734

Date