

SURVEY & REMONUMENTATION

MAY 28 1997

LAND CORNER RECORDATION CERTIFICATE Filing Requirement of Act 74, Mich. P.A. 1970

For corners in **COMMISSION**
Kalamazoo

Located in:

Corner Code #

(County)

Charleston

1. Public Land Survey

T2S R9W

I-11

T R

T R

T R

T R

2. Property Controlling
in Section

S

T R

S

T R

3. Miscellaneous
Property in Sec.

S

T R

S

T R

CLERK - REGISTER

LIBER

STATE OF MICHIGAN
COUNTY OF KALAMAZOO
RECEIVED FOR RECORD
'96 AUG 26 PM 4 00
2 PAGE 043

Register of Deeds Stamp & File Number

4. Lot No. , Recorded Plat

5. Private Claims

I, Robert E. Snell, in a field survey on May 8, 1996 do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and /or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

**RATIFIED
BY KALAMAZOO COUNTY
REMONUMENTATION
PEER GROUP 7-18-1996**

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2		6		5		4		3		2		1	
3													
4		7		8		9		10		11		12	
5													
6		18		17		16		15		14		13	
7													
8		19		20		21		22		23		24	
9													
10		30		29		28		27		26		25	
11													
12		31		32		33		34		35		36	
13													

A. Description of original monument and accessories and/or subsequent restoration:

1826: United States Government surveyors; set post common to Sections 26, 27, 34 and 35.
Wh. Oak 16" S 47° E 26 lks.
Wh. Oak 14" N 40° W 82 lks.

1876: F. Hodgman, County Surveyor; found stake, set iron stake and stones and noted without marks.
Hickory 8" S 51° E 82 lks.

1883: F. Hodgman, County Surveyor; found iron post and stone of resurvey and 1 witness of resurvey standing. Set same iron 4 ft. deep with earthen post over and brick and small stones around. This corner is in center of road and I found remains of tree

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:
N 40° W 82 lks.

1940: Wilkins and Wheaton Engr. Co.; found tile
6" Hickory S 20° E 93.44' 6" Hickory N 40° E 52.53'
8" Hickory S 15° W 161.30' 14" Maple N 60° E 85.80'

1996: Found 1/2"x12" long iron bar over tile 14" deep in monument box.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

I-11: Northeast corner of Section 34, T 2 S, R 9 W; ratified by the Kalamazoo County Remonumentation Program Peer Group on July 18, 1996 and is accepted as a careful and faithful perpetuation of the position of the original corner. Found 3" round tile as set by F. Hodgman, County Surveyor in 1883 remonumentation survey. Placed remonumentation sleeve in concrete over tile in monument box.

PK nail on South side 15" Hickory S 55° E 62.05'
PK nail on South side 22" Hickory N 42° E 52.77'
PK nail on East side 12" Wild Cherry N 40° W 47.95'
PK nail on North side 8" Triple Wild Cherry S 60° W 48.00'

Signed by Robert E. Snell Date 8-22-96
Surveyor's Michigan License No. 9734