



LC-000078
Page: 1 of 1
12/17/1999 02:03P
Bk-2 Pg-531

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

For corners in Oshtemo Twp.

Kalamazoo
(County)

Located in:

Corner Code #

1. Public Land Survey

T 2 S R 12 W

H-08

2. Property Controlling
in Section

S

T R

T R

T R

T R

T R

T R

3. Miscellaneous
Property in Sec.

S

T R

4. Lot No. _____ Recorded Plat _____

5. Private Claims _____

SURVEY &
REMONUMENTATION

FEB 08 2000

SECTION

Register of Deeds Stamp & File Number

I, Robert E. Snell, in a field survey on June 6, 1999 do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

This corner not established by original Government Surveyors.

1864: F. Stimson, County Surveyor; center of Section established by former survey and stone planted from which (a Balm of) Gilead 5' N. 5° E., 139 lks. ... Oak 12" S. 63° W., 97 lks.

1882 & 1884: E. Strong, County Surveyor; found alright.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

1999: Found 1/4" x 6" iron in monument box. Found stone with drill hole down 1.5' below surface, with traces of iron and small stones around stone. Stone is 15" to 18" long and about 6" in dia. Surface marker was 0.92' North and 0.28' East of drilled stone.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

H-08: Center of Section, Section 22, T. 2 S., R. 12 W., ratified by the Kalamazoo County Remonumentation Program Peer Group on July 15, 1999 and is accepted as the best available evidence of the position of the corner. This corner not set by original Government Surveyors. Found 15" to 18" long stone 6" in diameter with drill hole in the top. Stone set in 1864 by F. Stimson, County Surveyor. Placed 16" Harrison monument over stone in monument box.

PK Nail in West Side

28" Maple

N. 72° E.

74.77'

PK Nail in West Side

28" Maple

S. 10° E.

44.85'

PK Nail in North Side

32" Maple

S. 60° W.

61.40'

PK Nail in East Side

40" Maple

N. 18° W.

28.20'

Signed by Robert E. Snell
Surveyor's Michigan License No. 9734

Date 12/16/99

RATIFIED
BY KALAMAZOO COUNTY
REMONUMENTATION
PEER GROUP

7/15/99 R. E. Snell