

APR 01 1996

COMMISSION

LAND CORNER RECORDATION CERTIFICATE  
Filing Requirement of Act 74, Mich. P.A. 1970

STATE OF MICHIGAN  
COUNTY OF KALAMAZOO  
RECEIVED FOR RECORD  
95 DEC 8 AM 10 55

For corners in

KALAMAZOO  
(County)

Located in:

Corner Code #

Climax Twp.

1. Public Land Survey	T 3S R 9W	D10
	T R	
	T R	
	T R	
2. Property Controlling in Section	S T R	
	S T R	
3. Miscellaneous	S T R	
Property in Section	S T R	

*James D. Young*  
CLERK-REGISTER

LIBER 1 1386

Register of Deeds Stamp & File Number

4. Lot No. , Recorded Plat  
5. Private Claims

I, Gary D. Hahn, in a field survey on May 2,, 19 95, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Professional Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

**NOTE:** Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:  
Corner not set during original government survey.

1874 F. Hodgman "At int. 1/4 lines set stone and broken crockery."

1885 F. Hodgman "Stone of former survey."

1919 K.C.R.C. Stone and crockery. Conc. gate post S60°W 37.6'  
Conc. F. Cor. post E. 33.6'  
Walnut 22" N80°W 41.5'

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:  
Found 8" x 12" pointed stone with crockery around it 32" below road surface.  
Also found two accessories listed above in K.C.R.C. notes which fit found stone. See below.

RATIFIED  
BY KALAMAZOO COUNTY  
REMONUMENTATION  
PEER GROUP  
6-15-95



C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

D10, Center of Section 29, T3S, R9W, Ratified by Kalamazoo County Remonumentation Peer Group on June 15, 1995. The position of the found stone is accepted as the best available evidence of the position of the corner. (This position not established by original government surveyors.) Set 30" Harrison monument directly over point of stone in a monument box. SWly. corner of conc. corner fence post N89°E 33.99'  
Set P.K. nail in 38" Walnut N80°W 41.74'  
Set P.K. nail in P.P. S32°W 98.60'  
Set P.K. nail in 24" Oak N88°E 46.28'

Signed by

*Gary D. Hahn*

Date December 5, 1995

Surveyor's Michigan License No. 38116