

FEB 18 1994

COMMISSION

LAND CORNER RECORDATION CERTIFICATE  
Filing Requirement of Act 74, Mich. P.A. 1970

STATE OF MICHIGAN  
COUNTY OF KALAMAZOO  
RECEIVED FOR RECORD

'93 NOV 29 PM 2 22

For corners in

<u>Kalamazoo</u> (County)	Located In:	Corner Code #
Climax Township		
1. Public Land Survey	T <u>3</u> S <u>R</u> 9 W	<u>J-9</u>
	T <u>    </u> R <u>    </u>	<u>    </u>
	T <u>    </u> R <u>    </u>	<u>    </u>
	T <u>    </u> R <u>    </u>	<u>    </u>
2. Property Controlling in Section	S <u>    </u> T <u>    </u> R <u>    </u>	<u>    </u>
	S <u>    </u> T <u>    </u> R <u>    </u>	<u>    </u>
3. Miscellaneous Property in Sec.	S <u>    </u> T <u>    </u> R <u>    </u>	<u>    </u>
	S <u>    </u> T <u>    </u> R <u>    </u>	<u>    </u>
4. Lot No. <u>          </u> , Recorded Plat <u>          </u>		
5. Private Claims <u>          </u>		

*James J. Young*  
CLERK-REGISTER

LIBER 1 PG 1041

Register of Deeds Stamp & File Number

I, John G. Kester, in a field survey on August 11, 1993, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

	A	B	C	D	E	F	G	H	I	J	K	L	M
2	6	5	4	3	2	1							
3													
4	7	8	9	10	11	12							
5													
6	18	17	16	15	14	13							
7													
8	19	20	21	22	23	24							
9													
10	30	29	28	27	26	25							
11													
12	31	32	33	34	35	36							
13													

A. Description of original monument and accessories and/or subsequent restoration:  
Corner Post established by U S Government Deputy Surveyor Robert Clark, 1826,  
Accessories: Beech 7 S17W 7, Beech 12 N63E 17.  
Remonumentation by F. Hodgeman, 1883, Found Stone, Charcoal and old Stake bottom with side Stones 50 Lks East & West and Stump of one witness of resurvey N E, all agreeing together. Bored 3' and put in 3' Earthen Posts with Stone around.  
Accessories: Elm 6" N75<sup>1</sup>/<sub>2</sub>E 47 Lks, Elm 9" S51 3/4E 42 Lks.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:  
Original Corner and Accessories not recovered.  
Found Stone above Solid Clay Tile with X on top 4.5' below road surface as called for in 1883 Remonumentation by F. Hodgeman.

RATIFIED  
BY KALAMAZOO COUNTY  
REMONUMENTATION  
PEER GROUP  
9-16-93

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:  
J-9, S<sup>1</sup>/<sub>4</sub> Corner Section 23, T3S-R9W, Ratified by Kalamazoo County Remonumentation Program Peer Group on September 16, 1993. Found Stone above Solid Clay Tile with X on top as called for in 1883 Remonumentation and is accepted as a careful and faithful perpetuation of the Original Corners position. Placed 30" Harrison Monument above Stone and Solid Clay Tile with X on top and placed Monument Box over Corner.

Set P.K. Nail in P.P. N45W 40.59'  
Set P.K. Nail in 19" Elm S40W 55.31'  
Set P.K. Nail in 17" Cherry S30E 50.16'  
Set P.K. Nail in 14" Elm N30 E 66.21'

Signed by John G. Kester

Date 11-29-93

Surveyor's Michigan License No. 16046

Kalamazoo County Road Commission