

# SURVEY & REMONUMENTATION

APR 27 1995

COMMISSION

## LAND CORNER RECORDATION CERTIFICATE Filing Requirement of Act 74, Mich. P.A. 1970

LIBER

1 PG 1244

STATE OF MICHIGAN  
COUNTY OF KALAMAZOO  
RECEIVED FOR RECORD  
94 DEC 30 AM 9 18

CLERK-REGISTER

For corners in

Kalamazoo

(County)

Brady Township

Located In:

Corner Code =

1. Public Land Survey

T 4 S R 10 W

E-12

T R

T R

T R

2. Property Controlling  
in Section

S T R

S T R

3. Miscellaneous

S T R

Property in Sec.

S T R

4. Lot No. , Recorded Plat

5. Private Claims

I, Robert E. Snell in a field survey on June 7, 19 94, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

**NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.**

A. Description of original monument and accessories and/or subsequent restoration:

1826: U.S. Government Survey; Set 1/4 Section Post.

W. Oak 16" South 10° East 17 Lks

W. Oak 16" North 25° West 32½ Lks

1863: F. Stimson, County Surveyor; Notes obliterated.

1919: Kalamazoo County Road Commission; field notes and plan sheet show stone and later placed iron.

School Pump North 50° West 103.5' Southeast Corner Schoolhouse Northwest 155.8'

School Fence North On Line Sycamore North 68° East 112.70'

Fence Corner North 70° East 120.00'

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

1994: Found 1" x 36" iron in Center Line of "XY" Avenue. The iron fit fence corner witness and corner of school house (now a residence). Dug and found no other evidence.

RATIFIED  
BY KALAMAZOO COUNTY  
REMONUMENTATION  
PEER GROUP  
9-15-94

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

E-12 East 1/4 Post Section 32, T. 4 S., R. 10 W., Ratified by the Kalamazoo County Remonumentation Program Peer Group on September 15, 1994. Found 1" x 36" iron rod from 1919 witnesses called for on 1919 Kalamazoo County Road Commission plans and is accepted as a careful and faithful perpetuation of the position of the original corner. Removed iron and placed a 20" Harrison monument with monument box over.

Center Line "XY" Avenue

On Line

Southeast Corner of Schoolhouse

Exist. Double Head Nail in East Side Telephone Pole

PK Nail in West Side 60" Oak

PK Nail in Northeast Side 36" Oak

Center Line 28th Street

North 22° West 155.80'

North 28° East 30.85'

South 24° East 47.94'

South 56° East 62.78'

West 2.6'

Signed by

*Robert E. Snell*

Date

12/28/94

Surveyor's Michigan License No.

9734