

SURVEY &
REMONUMENTATION

STATE OF MICHIGAN
COUNTY OF KALAMAZOO
RECEIVED FOR RECORD

1
2
APR 27 1995

LAND CORNER RECORDATION CERTIFICATE

Filing Requirement of Act 74, Mich. P.A. 1970

DEC 14 PM 2 38

COMMISSION

For corners in

Kalamazoo

(County)

Located In:

Corner Code #

Schoolcraft Township

T 4 S R 11 W

A-4

1. Public Land Survey

T R

T R

T R

T R

2. Property Controlling
in Section

S T R

S T R

3. Miscellaneous
Property in Sec.

S T R

S T R

James J. Jans

CLERK-REGISTER

LIBER

1 PG 1202

Register of Deeds Stamp & File Number

4. Lot No. Recorded Plat

5. Private Claims

I, Robert E. Snell, in a field survey on May 17, 19 94

do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

This Position not established by original government surveyors.

1940: Wilkins & Wheaton Engineering; Established Corner on Range Line at a bisection of Northwest Corner Section 7, T. 4 S., R. 11 W. (A-3) and Southwest Corner Section 7, T. 4 S., R. 11 W. (A-5). Set large stone.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

1994: Found large stone with "X" on top as set in 1940 survey.

	A	B	C	D	E	F	G	H	I	J	K	L	M
2	6		5		4		3		2		1		
3													
4	7		8		9		10		11		12		
5													
6	16		17		16		15		14		13		
7													
8	19		20		21		22		23		24		
9													
10	30		29		28		27		26		25		
11													
12	31		32		33		34		35		36		
13													

RATIFIED
BY KALAMAZOO COUNTY
REMONUMENTATION
PEER GROUP
9-15-94

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

A-4 West 1/4 Post Section 7, T. 4 S., R. 11 W., Ratified by the Kalamazoo County Remonumentation Program Peer Group on September 15, 1994. Found large stone as set in 1940 survey by Wilkins & Wheaton Engineering Company. This position not established by original government surveyors. This monument is accepted as the best available evidence of the position of the corner. Removed stone and placed 20" Harrison monument and monument box. Set stone as a witness between pavement and plow line of field.

Notch in Stone South 68° East 24.00'
CL Telephone Pedestal South 14° East 192.48'
CL Center Pivot Irrigation North 60° West 600'±
CL Center Pivot Irrigation South 40° West 900'±
East 1/4 Post Section 12, T. 4 S., R. 12 W., South 20.13'

Signed by

Robert E. Snell

Date

12-14-94

Surveyor's Michigan License No.

9734