SURVEY & REMONUMENTATION

2	
J	

Property in Sec.

APR 2 7 1995

LAND CORNER RECORDATION CERTIFICATE Filing Requirement of Act 74, Mich. P.A. 1970

STATE OF	MICHIGAN
COUNTY OF	KALAMAZOC
RECEIVED F	OR RECORD

'94 DEC 14 PM 2 38

For corners in COMMISSION	ļ.		
Kalamazoo	Located In:	Corner Code ##	
Prairie Ronde Township			
Public Land Survey	T 4 S R 12 W	<u>M-4</u>	

R 2. Property Controlling _ R . Τ R in Section Ţ 3. Miscellaneous

R.

CLERK-REGISTER

1 FG1199 **IRER**

Register of Deeds Stamp & File Number

__ , Recorded Plat _ 4. Lot No. _ 5. Private Claims __

, ₁₉ _94 May 20 I, Robert E. Snell, in a field survey on do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

U.S. Government Survey; Set 1/4 Section Post, in prairie and raised mound. The indian village of "Prairie Ronde" bears from this point North 84° West, distance about 2 1/2 miles.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

1994: Dug and found nothing except a previously dug hole. Placed a 20" Harrison monument for East 1/4 Post Section 12, T. 4 S., R. 12 W. (M-4) on line between Southeast Corner Section 12, T. 4 S., R. 12 W. (M-5) and West 1/4 Post Section 7, T. 4 S., R. 11 W. (A-5), 20.13 feet (1/2 Government jog) South of West 1/4 Post Section 7.

> RATIFIED BY KALAMAZOO COUNTY REMONUMENTATION. PESR CROUP 9-15-94

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

M-4 East 1/4 Post Section 12, T. 4 S., R. 12 W., Ratified by the Kalamazoo County Remonumentation Program Peer Group on September 15, 1994. Placed a 20" Harrison monument at the corner as described in "B" above, and is accepted as a careful and faithful reestablishment of the position of the original corner. Placed monument box over monument

North 60° East 25.52' Stone South 06° East 172.55' Telephone Pedestal CL Top of South 30° East 900'+ Pivot Irrigation Center of North 68° East Pivot Irrigation 600°± Center of 20.13' West 1/4 Post Section 7 Schoolcraft North CL 12th Street West

Signed by

9734 Surveyor's Michigan License No. .

_ Date _

FORM APPROVED BY MICHIGAN STATE BOARD OF LAND SURVEYORS, JAN. 28, 1971

REVISED JAN., 1983