

LAND CORNER RECORDATION CERTIFICATE  
Filing Requirement of Act 74, Mich. P.A. 1970

For corners in  
LAKE

Located In:

Corner Code #/

1. Public Land Survey

T 18 N R 13 W

J-2

T R

T R

T R

2. Property Controlling  
in Section

S 2

T R

8, 9, 12

S T R

3. Miscellaneous  
Property in Sec

S

T R

4. Lot No. , Recorded Plat

5. Private Claims

Register of Deeds Stamp & File Number

I, CARL F. ROSER, in a field survey on JUNE 7, 19 84,  
do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned  
in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the  
current manual of survey instructions of the United States Department of the Interior, Bureau of Land  
Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5  
above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a  
Court of Law, established, re-established, monumented, re-monumented, recovered, found as  
expressed below.

**NOTE: Not more than 4 corners, all in the same town and range, may be recorded  
on this certificate.**

A. Description of original monument and accessories and/or subsequent restoration:

J-2

8

9

12

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

J-2

8

9

12

ESTABLISH CTR SEC 2 AT  
INTERSECTING 1/4 LINES.

ESTABLISH SW COR, SE1/4, NW1/4,  
SEC 2 PER STANDARD BLM  
INSTRUCTIONS. THE FD CONC  
MON, S 87°W 2.5' IS PROBABLY  
RESULT OF LAKE CO. RD. CONN.  
SURVEY.

ESTABLISH SW COR, SE1/4, NE1/4, SEC 2 PER STD BLM  
INSTRUCTIONS.

ESTABLISH NW COR, SW1/4, SE1/4,  
SEC 2 PER STD BLM  
INSTRUCTIONS.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

J-2

8

9

12

DROVE 5/8"X34" RE-ROD W/RLS  
CAP, SET CED POST W/ LOC TAG  
4" MAPLE N 55°W 27.0'  
7" R OAK DUE N 12.2'  
3" N OAK S 20°W 8.5'  
CROOKED  
TRAIL RD DUE S 147'

DROVE 5/8"X34" RE-ROD W/RLS  
CAP, SET CED POST W/ LOC TAG  
7" R OAK N 30°W 7.3'  
4" MAPLE N 60°E 20.8'  
6" MAPLE S 15°W 17.0'  
FD CONC MON S 87°W 2.52'

DROVE 5/8" RE-ROD W/ RLS CAP,  
SET CED POST W/ LOC TAG  
7" MAPLE IN  
CLUMP OF 3 N 55°W 9.3'  
6" MAPLE DUE N 15.0'  
8" R OAK S 35°E 59.9'  
7" MAPLE S 25°W 70.7'

DROVE 5/8" X 34" RE-ROD W/ RLS  
CAP, SET CED POST W/ LOC TAG  
8" OAK N 50°E 5.7'  
3" MAPLE S 20°E 8.1'  
8" W OAK S 85°W 24.1'

Signed by Carl F. Roser 03-16-88 Date

Surveyor's Michigan License No. 12028

